Telefon: +49 (0) 6135 931069
Telefax: +49 (0) 6135 931070
www.peak-electronics.de
info@peak-electronics.de

M6 SERIES P10TG-XXXXE2:1M 1.5 KV ISOLATED 2 W REGULATED SINGLE OUTPUT DIP24

Available Inputs:
12, 24 and 48 VDC Wide Input 2:1
Available Outputs:
3.3, 5, 12, 15 and 18 VDC
Other specifications please enquire.


Electrical Specifications
(Typical at + 25° C, nominal input voltage, rated output current unless otherwise specified)

Input Specifications	
Voltage range	9 - 18 VDC (12 VDC), 18 - 36 VDC (24 VDC) 36 - 72 VDC (48 VDC)
Filter	Pi Network
Isolation Specifications	
Rated voltage	1500 Vdc
Leakage current	1 mA
Resistance	10^9 Ohm
Capacitance	80 pF typ.
Output Specifications	
Voltage accuracy	+/- 1 % typ. +/-2% max.
Ripple and noise (at 20 MHz BW)	60 mV p-p, max.
Short circuit protection	Continuous , restart automatic
Line voltage regulation	+/- 0,5 % max.
Load voltage regulation	+/- 0,5 % max.
Temperature coefficient	+/- 0,02 % / °C
General Specifications	
Efficiency	70 % to 85 %
Switching frequency	250 KHz, typ.
Environmental Specifications	
Operating temperature (ambient)	-40°C to +85°C
Storage temperature	- 55 °C to + 125 °C
Derating	See graph
Humidity	Up to 90 %, non condensing
Cooling	Free air convection
Physical Characteristics	
Dimensions	31,75 x 20,32 x 10,16 mm 1,25 x 0,80 x 0,40 inches
Weight	16,3 g
Case material	Nickel Coated Copper


Examples of Partnumbers/Modelcode

PART NO.	INPUT VOLTAGE (VDC) Nominal	INPUT CURRENT NO LOAD	INPUT CURRENT FULL LOAD	OUTPUT VOLTAGE (VDC)	OUTPUT CURRENT (max. mA)	EFFICIENCY FULL LOAD (% TYP.)
P10TG-1205E2:1M	9-18	12	225	5	400	74
P10TG-1215E2:1M	9-18	12	208	15	134	80
P10TG-2405E2:1M	18-36	12	113	5	400	74
P10TG-2412E2:1M	18-36	12	105	12	167	79
P10TG-2415E2:1M	18-36	12	104	15	134	80
P10TG-4805E2:1M	36-72	10	56	5	400	75
P10TG-4812E2:1M	36-72	10	53	12	167	79

Dimensions



Derating Graph and Pinning



Pin	Connection		
#	Single		
1	+	V	Input
2			NC
3			NC
9			Omitted
10	-	V	Output
11	+	V	Output
12	-	V	Input
13	-	V	Input
14	+	V	Output
15	-	V	Output
16			Omitted
22			NC
23			NC
24	+	V	Input

Specification can be changed without notice. Copyright PEAK electronics GmbH

REV:2 / 09.2001

ООО «НИОКРсистемс» - это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

Наша компания это:

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование
- Работаем по 275 ФЗ

ООО «НИОКР СИТЕМС»
Москва, 125362, Россия, ул. Вишневая, д. 9, к. 1, Блок 104 а и 104 в

Телефон: 8 (495) 268-14-82
Email: n@nsistems.ru

ИНН: 7735154786
ОГРН: 1167746717709