

### APPLICATIONS

- Rectification.
- Freewheel Diode.
- DC Motor Control.
- Power Supplies.
- Welding.
- Battery Chargers.

### KEY PARAMETERS

|             |        |
|-------------|--------|
| $V_{RRM}$   | 1800V  |
| $I_{F(AV)}$ | 2320A  |
| $I_{FSM}$   | 41250A |


### FEATURES

- Double Side Cooling.
- High Surge Capability.

### VOLTAGE RATINGS

| Type Number | Repetitive Peak Reverse Voltage<br>$V_{RRM}$<br>V | Conditions                 |
|-------------|---------------------------------------------------|----------------------------|
| TR2002SF18  | 1800                                              | $V_{RSM} = V_{RRM} + 100V$ |
| TR2002SF17  | 1700                                              |                            |
| TR2002SF16  | 1600                                              |                            |
| TR2002SF15  | 1500                                              |                            |
| TR2002SF14  | 1400                                              |                            |
| TR2002SF13  | 1300                                              |                            |

Lower voltage grades available.



Outline type code: F  
See Package Details for further information.

### CURRENT RATINGS

| Symbol                                 | Parameter                           | Conditions                                          | Max. | Units |
|----------------------------------------|-------------------------------------|-----------------------------------------------------|------|-------|
| <b>Double Side Cooled</b>              |                                     |                                                     |      |       |
| $I_{F(AV)}$                            | Mean forward current                | Half wave resistive load, $T_{case} = 100^{\circ}C$ | 2320 | A     |
| $I_{F(RMS)}$                           | RMS value                           | $T_{case} = 100^{\circ}C$                           | 3644 | A     |
| $I_F$                                  | Continuous (direct) forward current | $T_{case} = 100^{\circ}C$                           | 3300 | A     |
| <b>Single Side Cooled (Anode side)</b> |                                     |                                                     |      |       |
| $I_{F(AV)}$                            | Mean forward current                | Half wave resistive load, $T_{case} = 100^{\circ}C$ | 1345 | A     |
| $I_{F(RMS)}$                           | RMS value                           | $T_{case} = 100^{\circ}C$                           | 2110 | A     |
| $I_F$                                  | Continuous (direct) forward current | $T_{case} = 100^{\circ}C$                           | 1630 | A     |

# TR2002SF

## SURGE RATINGS

| Symbol    | Parameter                              | Conditions                                                                   | Max.               | Units  |
|-----------|----------------------------------------|------------------------------------------------------------------------------|--------------------|--------|
| $I_{FSM}$ | Surge (non-repetitive) forward current | 10ms half sine; $T_{case} = 175^{\circ}C$<br>$V_R = 50\% V_{RRM} - 1/4$ sine | 33.0               | kA     |
| $I^2t$    | $I^2t$ for fusing                      |                                                                              | $5.44 \times 10^6$ | $A^2s$ |
| $I_{FSM}$ | Surge (non-repetitive) forward current | 10ms half sine; $T_{case} = 175^{\circ}C$<br>$V_R = 0$                       | 41.25              | kA     |
| $I^2t$    | $I^2t$ for fusing                      |                                                                              | $8.5 \times 10^6$  | $A^2s$ |

## THERMAL AND MECHANICAL DATA

| Symbol        | Parameter                             | Conditions                                   |             | Min. | Max.  | Units         |
|---------------|---------------------------------------|----------------------------------------------|-------------|------|-------|---------------|
| $R_{th(j-c)}$ | Thermal resistance - junction to case | Double side cooled                           | dc          | -    | 0.022 | $^{\circ}C/W$ |
|               |                                       | Single side cooled                           | Anode dc    | -    | 0.038 | $^{\circ}C/W$ |
|               |                                       |                                              | Cathode dc  | -    | 0.052 | $^{\circ}C/W$ |
| $R_{th(c-h)}$ | Thermal resistance - case to heatsink | Clamping force 19.5kN with mounting compound | Double side | -    | 0.004 | $^{\circ}C/W$ |
|               |                                       |                                              | Single side | -    | 0.008 | $^{\circ}C/W$ |
| $T_{vj}$      | Virtual junction temperature          | Forward (conducting)                         |             | -    | 185   | $^{\circ}C$   |
|               |                                       | Reverse (blocking)                           |             | -    | 175   | $^{\circ}C$   |
| $T_{stg}$     | Storage temperature range             |                                              |             | -55  | 200   | $^{\circ}C$   |
| -             | Clamping force                        |                                              |             | 18.0 | 22.0  | kN            |

## CHARACTERISTICS

| Symbol    | Parameter             | Conditions                                                                  | Min. | Max.  | Units      |
|-----------|-----------------------|-----------------------------------------------------------------------------|------|-------|------------|
| $V_{FM}$  | Forward voltage       | At 3400A peak, $T_{case} = 25^{\circ}C$                                     | -    | 1.18  | V          |
| $I_{RRM}$ | Peak reverse current  | At $V_{RRM}$ , $T_{case} = 175^{\circ}C$                                    | -    | 50    | mA         |
| $Q_S$     | Total stored charge   | $I_F = 2000A$ , $dI_{RR}/dt = 3A/\mu s$<br>$T_{case} = 175C$ , $V_R = 100V$ | -    | 1500  | $\mu C$    |
| $I_{RR}$  | Peak recovery current |                                                                             | -    | 90    | A          |
| $V_{TO}$  | Threshold voltage     | At $T_{vj} = 175C$                                                          | -    | 0.74  | V          |
| $r_T$     | Slope resistance      | At $T_{vj} = 175C$                                                          | -    | 0.088 | m $\Omega$ |

## CURVES




Fig.1 Maximum (limit) forward characteristics




Fig.2 Dissipation curves




Fig.3 Maximum total stored charge




Fig. 4 Maximum reverse recovery current




Fig. 5 Surge (non-repetitive) forward current vs time (with 50%  $V_{RRM}$ ,  $T_{case} = 175C$ )





Fig. 6 Transient thermal impedance - junction to case - (C/W)

**PACKAGE DETAILS**

For further package information, please contact your local Customer Service Centre. All dimensions in mm, unless stated otherwise.  
DO NOT SCALE.

2 holes Ø3.6x2.0 deep (in both electrodes)



Nominal weight: 500g  
Clamping force: 19.6kN  $\pm$  10%

**Package outline type code: F**



**ООО «НИОКРсистемс»** - это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

### **Наша компания это:**

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование
- Работаем по 275 ФЗ