

# Schottky Rectifier, 100 A



PowerTab®



## FEATURES

- 175 °C max. operating junction temperature
- High frequency operation
- Low forward voltage drop
- Continuous high current operation
- Guard ring for enhanced ruggedness and long term reliability
- Screw mounting only
- Designed and qualified according to JEDEC-JESD47
- PowerTab® package
- Compliant to RoHS Directive 2002/95/EC


RoHS  
COMPLIANT

## PRODUCT SUMMARY

|                 |                  |
|-----------------|------------------|
| Package         | PowerTab®        |
| $I_{F(AV)}$     | 100 A            |
| $V_R$           | 100 V            |
| $V_F$ at $I_F$  | 0.82 V           |
| $I_{RM}$        | 180 mA at 125 °C |
| $T_J$ max.      | 175 °C           |
| Diode variation | Single die       |
| $E_{AS}$        | 9 mJ             |

## DESCRIPTION

The VS-100BGQ100 Schottky rectifier has been optimized for low reverse leakage at high temperature.

The proprietary barrier technology allows for reliable operation up to 175 °C junction temperature. Typical applications are in switching power supplies, converters, reverse battery protection, and redundant power subsystems.

## MAJOR RATINGS AND CHARACTERISTICS

| SYMBOL      | CHARACTERISTICS               | VALUES      | UNITS |
|-------------|-------------------------------|-------------|-------|
| $I_{F(AV)}$ | Rectangular waveform          | 100         | A     |
|             | $T_C$                         | 124         | °C    |
| $V_{RRM}$   |                               | 100         | V     |
| $I_{FSM}$   | $t_p = 5 \mu s$ sine          | 6300        | A     |
| $V_F$       | 100 A <sub>pk</sub> (typical) | 0.77        | V     |
|             | $T_J$                         | 125         | °C    |
| $T_J$       | Range                         | - 55 to 175 | °C    |

## VOLTAGE RATINGS

| PARAMETER                            | SYMBOL    | 100BGQ100 | UNITS |
|--------------------------------------|-----------|-----------|-------|
| Maximum DC reverse voltage           | $V_R$     | 100       | V     |
| Maximum working peak reverse voltage | $V_{RWM}$ |           |       |

## ABSOLUTE MAXIMUM RATINGS

| PARAMETER                                           | SYMBOL      | TEST CONDITIONS                                                                                                     | VALUES | UNITS |
|-----------------------------------------------------|-------------|---------------------------------------------------------------------------------------------------------------------|--------|-------|
| Maximum average forward current                     | $I_{F(AV)}$ | 50 % duty cycle at $T_C = 124$ °C, rectangular waveform                                                             | 100    | A     |
| Maximum peak one cycle non-repetitive surge current | $I_{FSM}$   | 5 $\mu s$ sine or 3 $\mu s$ rect. pulse                                                                             | 6300   | A     |
|                                                     |             | 10 ms sine or 6 ms rect. pulse                                                                                      | 800    |       |
| Non-repetitive avalanche energy                     | $E_{AS}$    | $T_J = 25$ °C, $I_{AS} = 2$ A, $L = 4.5$ mH                                                                         | 9      | mJ    |
| Repetitive avalanche current                        | $I_{AR}$    | Current decaying linearly to zero in 1 $\mu s$<br>Frequency limited by $T_J$ maximum $V_A = 1.5 \times V_R$ typical | 2      | A     |

**ELECTRICAL SPECIFICATIONS**

| PARAMETER                      | SYMBOL         | TEST CONDITIONS                                                                             |                                     | VALUES |      | UNITS            |
|--------------------------------|----------------|---------------------------------------------------------------------------------------------|-------------------------------------|--------|------|------------------|
|                                |                |                                                                                             |                                     | TYP.   | MAX. |                  |
| Forward voltage drop           | $V_{FM}^{(1)}$ | 50 A                                                                                        | $T_J = 25\text{ }^{\circ}\text{C}$  | 0.83   | 0.86 | V                |
|                                |                | 100 A                                                                                       |                                     | 1.01   | 1.08 |                  |
|                                |                | 50 A                                                                                        | $T_J = 125\text{ }^{\circ}\text{C}$ | 0.66   | 0.7  |                  |
|                                |                | 100 A                                                                                       |                                     | 0.77   | 0.82 |                  |
| Reverse leakage current        | $I_{RM}^{(1)}$ | $T_J = 25\text{ }^{\circ}\text{C}$                                                          | $V_R = \text{Rated } V_R$           | 22     | 300  | $\mu\text{A}$    |
|                                |                | $T_J = 125\text{ }^{\circ}\text{C}$                                                         |                                     | 14     | 18   | mA               |
| Maximum junction capacitance   | $C_T$          | $V_R = 5\text{ }V_{DC}$ , (test signal range 100 kHz to 1 MHz) $25\text{ }^{\circ}\text{C}$ |                                     | 1320   |      | pF               |
| Typical series inductance      | $L_S$          | Measured from tab to mounting plane                                                         |                                     | 3.5    |      | nH               |
| Maximum voltage rate of change | $dV/dt$        | Rated $V_R$                                                                                 |                                     | 10 000 |      | V/ $\mu\text{s}$ |

**Note**(1) Pulse width < 300  $\mu\text{s}$ , duty cycle < 2 %**THERMAL - MECHANICAL SPECIFICATIONS**

| PARAMETER                                      | SYMBOL                            | TEST CONDITIONS                      | VALUES      | UNITS               |
|------------------------------------------------|-----------------------------------|--------------------------------------|-------------|---------------------|
| Maximum junction and storage temperature range | T <sub>J</sub> , T <sub>Stg</sub> |                                      | - 55 to 175 | °C                  |
| Maximum thermal resistance, junction to case   | R <sub>thJC</sub>                 | DC operation                         | 0.50        | °C/W                |
| Typical thermal resistance, case to heatsink   | R <sub>thCS</sub>                 | Mounting surface, smooth and greased | 0.30        |                     |
| Approximate weight                             |                                   |                                      | 5           | g                   |
|                                                |                                   |                                      | 0.18        | oz.                 |
| Mounting torque                                | minimum                           |                                      | 1.2 (10)    | N · m<br>(lbf · in) |
|                                                | maximum                           |                                      | 2.4 (20)    |                     |
| Marking device                                 |                                   | Case style PowerTab®                 | 100BGQ100   |                     |




Fig. 1 - Maximum Forward Voltage Drop Characteristics




Fig. 2 - Typical Values of Reverse Current vs. Reverse Voltage





Fig. 3 - Typical Junction Capacitance vs. Reverse Voltage


Fig. 4 - Maximum Thermal Impedance  $Z_{thJC}$  Characteristics




Fig. 5 - Maximum Allowable Case Temperature vs. Average Forward Current




Fig. 6 - Forward Power Loss Characteristics




Fig. 7 - Maximum Non-Repetitive Surge Current




Fig. 8 - Unclamped Inductive Test Circuit

#### Note

- (1) Formula used:  $T_C = T_J - (P_d + P_{dREV}) \times R_{thJC}$ ;  
 $P_d$  = Forward power loss =  $I_{F(AV)} \times V_{FM}$  at  $(I_{F(AV)}/D)$  (see fig. 6);  
 $P_{dREV}$  = Inverse power loss =  $V_{R1} \times I_R (1 - D)$ ;  $I_R$  at  $V_{R1} = 80\%$  rated  $V_R$



**ORDERING INFORMATION TABLE**


|             |     |     |                               |     |
|-------------|-----|-----|-------------------------------|-----|
| Device code | VS- | 100 | BGQ                           | 100 |
|             | 1   | 2   | 3                             | 4   |
|             | 1   | -   | Vishay Semiconductors product |     |
|             | 2   | -   | Current rating                |     |
|             | 3   | -   | Essential part number         |     |
|             | 4   | -   | Voltage code = $V_{RRM}$      |     |

| LINKS TO RELATED DOCUMENTS |                                                                        |
|----------------------------|------------------------------------------------------------------------|
| Dimensions                 | <a href="http://www.vishay.com/doc?95240">www.vishay.com/doc?95240</a> |
| Part marking information   | <a href="http://www.vishay.com/doc?95370">www.vishay.com/doc?95370</a> |
| Application note           | <a href="http://www.vishay.com/doc?95179">www.vishay.com/doc?95179</a> |



## PowerTab®

**DIMENSIONS** in millimeters (inches)





## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.



**ООО «НИОКРсистемс»** - это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

### **Наша компания это:**

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование
- Работаем по 275 ФЗ