
LOW-JITTER CRYSTAL OSCILLATOR

EG-2001CA

- Generates high frequency clock with fundamental mode.
- Very low jitter and low phase noise.
- Ceramic package with 1.4 mm Max. thickness.
- Excellent shock resistance and environmental capability.
- Low current consumption due to use of C-MOS technology.
- Provided with output enable function.




Specifications (characteristics)

Item		Symbol	Specifications	Remarks
Output frequency range		f_0	106.2500 MHz to 166.0000 MHz	Please contact us for inquiries about the available frequency
Power source voltage	Max. supply voltage	V_{DD}-GND	-0.5 V to +7.0 V	
	Operating voltage	V_{DD}	3.3 V±0.3 V	
Temperature range	Storage temperature	T_{STG}	-55 °C to +100 °C	
	Operating temperature	T_{OPR}	0 °C to +70 °C	
Frequency stability		$\Delta f/f_0$	±100 x 10^{-6} *	
Current consumption		Iop	50 mA Max.	No load condition
Output disable current		I_{OE}	10 µA Max.	OE=GND
Duty	C-MOS level	tw/t	45 % to 55 %	50 % V_{DD}, $C_L \leq$ Max.
	TTL level		40 % to 60 %	1.4V Level, $C_L \leq$ Max.
Output voltage		V_{OH}	V_{DD}-0.4 V Min.	I_{OH}= -8 mA
		V_{OL}	0.4 V Max.	I_{OL}= 8 mA
Output load condition (fan out)		C_L	25 pF Max.	$f_0 \leq$ 135.0000 MHz
			15 pF Max.	$f_0 >$ 135.0000 MHz
Output enable disable input voltage		V_{IH}	0.7 V_{DD} Min.	OE
		V_{IL}	0.3 V_{DD} Max.	OE
Output rise time	C-MOS level	t_{TLH}	2 ns Max.	C-MOS load: 20 %→80 % V_{DD}
	TTL level		1.5 ns Max.	TTL load: 0.8 V→2.0 V
Output fall time	C-MOS level	t_{THL}	2 ns Max.	C-MOS load: 80 %→20 % V_{DD}
	TTL level		1.5 ns Max.	TTL load: 2.0 V→0.8 V
Oscillation start up time		t_{OSC}	10 ms Max.	Time at 3.0 V to be 0 s
Deterministic Jitter		t_{DJ}	5.0 ps Typ.	Peak to peak
Random Jitter		t_{RJ}	3.0 ps Typ.	rms
Accumulated Jitter		t_{jacc}	4.0 ps Typ.	Long ferm

*Frequency stability is including variation in reflow soldering drift, operating temperature range, operating voltage range, load change and Aging.


External dimensions

(Unit: mm)



Recommended soldering pattern

(Unit: mm)



ООО «НИОКРсистемс» - это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

Наша компания это:

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование
- Работаем по 275 ФЗ

ООО «НИОКР СИТЕМС»
Москва, 125362, Россия, ул. Вишневая, д. 9, к. 1, Блок 104 а и 104 в

Телефон: 8 (495) 268-14-82
Email: n@nsistems.ru

ИНН: 7735154786
ОГРН: 1167746717709