

# FDW256P

## 30V P-Channel PowerTrench<sup>®</sup> MOSFET

### General Description



This PChannel MOSFET is a rugged gate version of Fairchild Semiconductor's advanced PowerTrench process. It has been optimized for power management applications requiring a wide range of gate drive voltage ratings (4.5V – 25V).

### Applications

- Battery protection
- DC/DC conversion
- Power management
- Load switch

### Features

- –8 A, –30 V  $R_{DS(ON)} = 13.5\text{ m}\Omega$  @  $V_{GS} = -10\text{ V}$   
 $R_{DS(ON)} = 20\text{ m}\Omega$  @  $V_{GS} = -4.5\text{ V}$
- Extended  $V_{GSS}$  range ( $\pm 25\text{V}$ ) for battery applications
- High performance trench technology for extremely low  $R_{DS(ON)}$
- Low profile TSSOP-8 package



### Absolute Maximum Ratings $T_A = 25^\circ\text{C}$ unless otherwise noted

| Symbol         | Parameter                                        | Ratings     | Units            |
|----------------|--------------------------------------------------|-------------|------------------|
| $V_{DSS}$      | Drain-Source Voltage                             | –30         | V                |
| $V_{GSS}$      | Gate-Source Voltage                              | $\pm 25$    | V                |
| $I_D$          | Drain Current – Continuous (Note 1)              | –8          | A                |
|                | – Pulsed                                         | –50         |                  |
| $P_D$          | Power Dissipation (Note 1a)<br>(Note 1b)         | 1.3         | W                |
|                |                                                  | 0.6         |                  |
| $T_J, T_{STG}$ | Operating and Storage Junction Temperature Range | –55 to +150 | $^\circ\text{C}$ |

### Thermal Characteristics

|                 |                                                                |     |                    |
|-----------------|----------------------------------------------------------------|-----|--------------------|
| $R_{\theta JA}$ | Thermal Resistance, Junction-to-Ambient (Note 1a)<br>(Note 1b) | 96  | $^\circ\text{C/W}$ |
|                 |                                                                | 208 |                    |

### Package Marking and Ordering Information

| Device Marking | Device  | Reel Size | Tape width | Quantity   |
|----------------|---------|-----------|------------|------------|
| 256P           | FDW256P | 13"       | 16mm       | 2500 units |

**Electrical Characteristics** $T_A = 25^\circ\text{C}$  unless otherwise noted

| Symbol                                                 | Parameter                                             | Test Conditions                                                                                                                                                        | Min | Typ            | Max              | Units |
|--------------------------------------------------------|-------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|----------------|------------------|-------|
| Off Characteristics                                    |                                                       |                                                                                                                                                                        |     |                |                  |       |
| $BV_{DSS}$                                             | Drain–Source Breakdown Voltage                        | $V_{GS} = 0\text{ V}, I_D = -250\text{ }\mu\text{A}$                                                                                                                   | –30 |                |                  | V     |
| $\frac{\Delta BV_{DSS}}{\Delta T_J}$                   | Breakdown Voltage Temperature Coefficient             | $I_D = -250\text{ }\mu\text{A}$ , Referenced to 25°C                                                                                                                   |     | –23            |                  | mV/°C |
| $I_{DSS}$                                              | Zero Gate Voltage Drain Current                       | $V_{DS} = -24\text{ V}, V_{GS} = 0\text{ V}$                                                                                                                           |     |                | –1               | μA    |
| $I_{GSSF}$                                             | Gate–Body Leakage, Forward                            | $V_{GS} = 25\text{ V}, V_{DS} = 0\text{ V}$                                                                                                                            |     |                | 100              | nA    |
| $I_{GSSR}$                                             | Gate–Body Leakage, Reverse                            | $V_{GS} = -25\text{ V}, V_{DS} = 0\text{ V}$                                                                                                                           |     |                | –100             | nA    |
| On Characteristics (Note 2)                            |                                                       |                                                                                                                                                                        |     |                |                  |       |
| $V_{GS(th)}$                                           | Gate Threshold Voltage                                | $V_{DS} = V_{GS}, I_D = -250\text{ }\mu\text{A}$                                                                                                                       | –1  | –1.7           | –3               | V     |
| $\frac{\Delta V_{GS(th)}}{\Delta T_J}$                 | Gate Threshold Voltage Temperature Coefficient        | $I_D = -250\text{ }\mu\text{A}$ , Referenced to 25°C                                                                                                                   |     | 5              |                  | mV/°C |
| $R_{DS(on)}$                                           | Static Drain–Source On–Resistance                     | $V_{GS} = -10\text{ V}, I_D = -8.0\text{ A}$<br>$V_{GS} = -4.5\text{ V}, I_D = -6.5\text{ A}$<br>$V_{GS} = -10\text{ V}, I_D = -8.0\text{ A}, T_J = 125^\circ\text{C}$ |     | 11<br>16<br>15 | 13.5<br>20<br>19 | mΩ    |
| $I_{D(on)}$                                            | On–State Drain Current                                | $V_{GS} = -10\text{ V}, V_{DS} = -5\text{ V}$                                                                                                                          | –50 |                |                  | A     |
| $g_{FS}$                                               | Forward Transconductance                              | $V_{DS} = -5\text{ V}, I_D = -8.0\text{ A}$                                                                                                                            |     | 30             |                  | S     |
| Dynamic Characteristics                                |                                                       |                                                                                                                                                                        |     |                |                  |       |
| $C_{iss}$                                              | Input Capacitance                                     | $V_{DS} = -15\text{ V}, V_{GS} = 0\text{ V},$<br>$f = 1.0\text{ MHz}$                                                                                                  |     | 2267           |                  | pF    |
| $C_{oss}$                                              | Output Capacitance                                    |                                                                                                                                                                        |     | 599            |                  | pF    |
| $C_{rss}$                                              | Reverse Transfer Capacitance                          |                                                                                                                                                                        |     | 315            |                  | pF    |
| Switching Characteristics (Note 2)                     |                                                       |                                                                                                                                                                        |     |                |                  |       |
| $t_{d(on)}$                                            | Turn–On Delay Time                                    | $V_{DD} = -15\text{ V}, I_D = -1\text{ A},$<br>$V_{GS} = -10\text{ V}, R_{GEN} = 6\text{ }\Omega$                                                                      |     | 15             | 27               | ns    |
| $t_r$                                                  | Turn–On Rise Time                                     |                                                                                                                                                                        |     | 11             | 35               | ns    |
| $t_{d(off)}$                                           | Turn–Off Delay Time                                   |                                                                                                                                                                        |     | 78             | 125              | ns    |
| $t_f$                                                  | Turn–Off Fall Time                                    |                                                                                                                                                                        |     | 45             | 72               | ns    |
| $Q_g$                                                  | Total Gate Charge                                     | $V_{DS} = -15\text{ V}, I_D = -8.0\text{ A},$<br>$V_{GS} = -5.0\text{ V}$                                                                                              |     | 28             | 38               | nC    |
| $Q_{gs}$                                               | Gate–Source Charge                                    |                                                                                                                                                                        |     | 7              |                  | nC    |
| $Q_{gd}$                                               | Gate–Drain Charge                                     |                                                                                                                                                                        |     | 12             |                  | nC    |
| Drain–Source Diode Characteristics and Maximum Ratings |                                                       |                                                                                                                                                                        |     |                |                  |       |
| $I_S$                                                  | Maximum Continuous Drain–Source Diode Forward Current |                                                                                                                                                                        |     |                | –1.2             | A     |
| $V_{SD}$                                               | Drain–Source Diode Forward Voltage                    | $V_{GS} = 0\text{ V}, I_S = -1.2\text{ A}$ (Note 2)                                                                                                                    |     | –0.7           | –1.2             | V     |

**Notes:**

1.  $R_{\theta JA}$  is the sum of the junction-to-case and case-to-ambient thermal resistance where the case thermal reference is defined as the solder mounting surface of the drain pins.  $R_{\theta JC}$  is guaranteed by design while  $R_{\theta CA}$  is determined by the user's board design.

a)  $R_{\theta JA}$  is  $96\text{ }^\circ\text{C/W}$  (steady state) when mounted on a 1 inch<sup>2</sup> copper pad on FR-4.

b)  $R_{\theta JA}$  is  $208\text{ }^\circ\text{C/W}$  (steady state) when mounted on a minimum copper pad on FR-4.

2. Pulse Test: Pulse Width  $< 300\text{ }\mu\text{s}$ , Duty Cycle  $< 2.0\%$

## Typical Characteristics




Figure 1. On-Region Characteristics.




Figure 2. On-Resistance Variation with Drain Current and Gate Voltage.




Figure 3. On-Resistance Variation with Temperature.




Figure 4. On-Resistance Variation with Gate-to-Source Voltage.




Figure 5. Transfer Characteristics.




Figure 6. Body Diode Forward Voltage Variation with Source Current and Temperature.

## Typical Characteristics




Figure 7. Gate Charge Characteristics.




Figure 8. Capacitance Characteristics.




Figure 9. Maximum Safe Operating Area.




Figure 10. Single Pulse Maximum Power Dissipation.




Figure 11. Transient Thermal Response Curve.

Thermal characterization performed using the conditions described in Note 1b.  
Transient thermal response will change depending on the circuit board design.



## TRADEMARKS

The following includes registered and unregistered trademarks and service marks, owned by Fairchild Semiconductor and/or its global subsidiaries, and is not intended to be an exhaustive list of all such trademarks.

Build it Now™  
CorePLUS™  
CorePOWER™  
CROSSVOLT™  
CTL™  
Current Transfer Logic™  
EcoSPARK®  
EfficientMax™  
EZSWITCH™ \*  
  
  
Fairchild®  
Fairchild Semiconductor®  
FACT Quiet Series™  
FACT®  
FAST®  
FastvCore™  
FlashWriter® \*

FPS™  
F-PFS™  
FRFET®  
Global Power ResourceSM  
Green FPS™  
Green FPS™ e-Series™  
GTO™  
IntelliMAX™  
ISOPLANAR™  
MegaBuck™  
MICROCOUPLER™  
MicroFET™  
MicroPak™  
MillerDrive™  
MotionMax™  
Motion-SPM™  
OPTOLOGIC®  
OPTOPLANAR®  


PDP SPM™  
Power-SPM™  
PowerTrench®  
Programmable Active Droop™  
QFET®  
QS™  
Quiet Series™  
RapidConfigure™  
Saving our world, 1mW at a time™  
SmartMax™  
SMART START™  
SPM®  
STEALTH™  
SuperFET™  
SuperSOT™-3  
SuperSOT™-6  
SuperSOT™-8  
SuperMOS™  
SyncFET™



The Power Franchise®  
the power franchise  
TinyBoost™  
TinyBuck™  
TinyLogic®  
TINYOPTO™  
TinyPower™  
TinyPWM™  
TinyWire™  
  
UHC®  
Ultra FRFET™  
UniFET™  
VCX™  
VisualMax™

\* EZSWITCH™ and FlashWriter® are trademarks of System General Corporation, used under license by Fairchild Semiconductor.

## DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

## LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

## ANTI-COUNTERFEITING POLICY

Fairchild Semiconductor Corporation's Anti-Counterfeiting Policy. Fairchild's Anti-Counterfeiting Policy is also stated on our external website, [www.fairchildsemi.com](http://www.fairchildsemi.com), under Sales Support.

Counterfeiting of semiconductor parts is a growing problem in the industry. All manufacturers of semiconductor products are experiencing counterfeiting of their parts. Customers who inadvertently purchase counterfeit parts experience many problems such as loss of brand reputation, substandard performance, failed application, and increased cost of production and manufacturing delays. Fairchild is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. Fairchild strongly encourages customers to purchase Fairchild parts either directly from Fairchild or from Authorized Fairchild Distributors who are listed by country on our web page cited above. Products customers buy either from fairchild directly or from Authorized Fairchild Distributors are genuine parts, have full traceability, meet Fairchild's quality standards for handling and storage and provide access to Fairchild's full range of up-to-date technical and product information. Fairchild and our Authorized Distributors will stand behind all warranties and will appropriately address and warranty issues that may arise. Fairchild will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. Fairchild is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

## PRODUCT STATUS DEFINITIONS

### Definition of Terms

| Datasheet Identification | Product Status        | Definition                                                                                                                                                                                          |
|--------------------------|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Advance Information      | Formative / In Design | Datasheet contains the design specifications for product development. Specifications may change in any manner without notice.                                                                       |
| Preliminary              | First Production      | Datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design. |
| No Identification Needed | Full Production       | Datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve the design.                                               |
| Obsolete                 | Not In Production     | Datasheet contains specifications on a product that is discontinued by Fairchild Semiconductor. The datasheet is for reference information only.                                                    |



**ООО «НИОКРсистемс»** - это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

### **Наша компания это:**

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование
- Работаем по 275 ФЗ