

ACP-4320

Quiet 4U Rackmount Chassis Ready with Dual SAS/SATA HDD Trays



Features

- Supports either an ATX motherboard or a PICMG backplane with up to 15 slots
- Supports dual SAS/SATA HDD trays for data monitoring applications
- LED indicators and alarm notification for system fault detection and network connection
- Low noise system fans with fan speed control
- Built-in Intelligent System Module enables whole system fan control and remote manageability

Quiet

CE FCC RoHS

Specifications


Drive Bay	5.25"	Front-accessible	Internal
	3.5"	2	-
Cooling	Fan	2 SAS/SATA Trays + 1	-
	Air Filter	(mobile trays compatible with 2.5" HDD/SSD)	-
Front I/O Interface	USB	1 (12 cm /74 CFM) + 1 (6 cm /28 CFM)	-
	9-pin D-Sub	Yes	-
Miscellaneous	LED Indicators	2	-
	Remote Management	Power, HDD, temperature, fan, LAN1, and LAN2	-
	Rear Panel	Remote monitoring & alarm message ^{Note 1} : CPU/System fan speed, CPU/System temperature, motherboard voltage	-
Environment	Temperature	Remote control ^{Note 2} : Power on/off, iKVM	-
	Humidity	Advanced functions ^{Note 3} : System recovery, system protection	-
	Vibration (5 ~ 500 Hz)	Backplane version: One 9-pin D-Sub opening	-
	Shock	Motherboard version: Five 9-pin D-Sub and one 68-pin SCSI openings	-
Physical Characteristics	Dimensions (W x H x D)	Operating	Non-Operating
	Weight	0 ~ 40° C (32 ~ 104° F)	-20 ~ 60° C (-4 ~ 140° F)

Note 1: Advantech motherboards with I2C interface H/W monitor and SUSIAccess 2.1.1122 (P/N: 968EMLSAP2) or later version are required to enable full functions.

Note 2: Advantech motherboards with iAMT technology and SUSIAccess 2.1.1122 (P/N: 968EMLSAP2) or later version are required to enable full functions.


Note 3: SUSIAccess 2.1.1122 (P/N: 968EMLSAP2) or later version is required to enable these functions.

Front View




Inside View

Easy-to-maintain system fan



Dimensions

Unit: mm [inch]



Ordering Information

Model Name	Power Supply
Backplane Version	
ACP-4320BP-00BE	Without power supply, with ATX switch
Motherboard Version	
ACP-4320MB-00BE	Without power supply, with ATX switch

Optional Accessories

Part Number	Description
IDT-3120E	Mobile rack for converting a 3.5" drive bay to dual 2.5" SATA HDD trays
IDT-5230E	Mobile rack for converting dual 5.25" drive bays to three 3.5" SAS/SATA HDD trays

Power Supply Options

(For detailed power supply specs, please refer to Chapter 13)

Part Number	Watts	Specifications Input
PS8-300ATX-ZBE (ATX, PFC)	300W	AC 100 ~ 240 V (full range)
PS8-400ATX-ZE (ATX, PFC)	400W	AC 100 ~ 240 V (full range)
PS8-500ATX-ZE	500W	AC 100 ~ 240 V (full range)
RPS-300ATX-ZE (ATX, PFC) (1+1 redundant)	300W	AC 100 ~ 240 V (full range)
1757004393-01 (ATX, PFC) (1+1 redundant)	500W	AC 100 ~ 240 V (full range)

Spare Parts

Part Number	Description
1990001299	Fan filter 95 x 130 mm
1990001298	Door filter 150 x 68 mm
9662132020E	Black mobile tray to support 2.5"/3.5" HDD/SSD



ООО «НИОКРсистемс» - это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

Наша компания это:

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование
- Работаем по 275 ФЗ