VC-TXO-23SM

SMD VC-TCXO

- Low Profile
- 3.2 x 2.5 mm Footprint
- Highly stable output
- Pb Free/RoHS Compliant

The miniature VC-TXO-23SM is a compact SMD VC-TCXO. The 3.2 x 2.5 x 0.9 mm ceramic package is ideal for today's SMD manufacturing environment.

OPERATING CONDITIONS / ELECTRICAL CHARACTERISTICS

PARAMETERS	CONDITIONS	VC-TXO-23SM			UNITS
		MIN	TYP	MAX	
Frequency Range		10.000		40.000	MHz
Initial Frequency Tolerance	@ +25°C ±2°C			± 1.5	ppm
Stability Option A	-10 ~ +70°C			± 2.5	ppm
Stability Option B	-30 ~ +75°C			± 2.5	ppm
Stability Option C	-30 ~ +85°C			± 5.0	ppm
Input Voltage Change	+3.0VDC ±5%			± 0.3	ppm
Load Change	10KΩ±10%//10 pF ±10%			± 0.2	ppm
Aging	per year @ +25°C ±3°C			± 1.0	ppm
Storage Temperature		-40		+85	mA
Supply Voltage		+2.85	+3.0	+3.15	V DC
Input Current	Without Load			1.5	mA
Output Level		0.8			V p-p
Output Load	10KΩ//10 pF				
Output Waveform	Clipped sine wave (DC-coupling)				
Frequency Control Range	+1.5V DC ±1V Positive Slope	± 9		± 15	ppm
Control Voltage		+0.5	+1.5	+2.5	V DC
SSB phase noise	-130 dBc/Hz at 1 KHz offset				
Startup time				3.5	ms
IR reflow resistance				± 1.0	ppm
Reflow condition	+250°C ±10°C for 10 sec				

Developed Frequencies

10.000 MHz, 19.200 MHz, 19.680 MHz, 20.000 MHz & 26.000 MHz

DIMENSIONS (mm)




Figure 1) Top, Side and Bottom views

Pin Connections	
Pin #1	Vcon
Pin #2	GND
Pin #3	Output
Pin #4	+VDC




Figure 2) Suggested Land Pattern

PART NUMBERING GUIDE: Example VC-TXO-23SM-192-B

ECS - Series - Frequency Abbreviation - Stability

Series	Frequency Abbreviation	Stability
VC-TXO-23SM	192 = 19.200 MHz See Frequency Abbreviations (Pg 2)	A = ±2.5 ppm -10 ~ +75°C B = ±2.5 ppm -30 ~ +75°C C = ±5.0 ppm -30 ~ +85°C

1105 South Ridgeview Road • Olathe, KS 66062 • Phone: 913.782.7787 • Fax: 913.782.6991 • www.ecsxtal.com

Frequency Abbreviations

FREQUENCY MHz	CODE
10.000000	100
19.200000	192
19.680000	196.8
19.800000	198
20.000000	200
26.000000	260





Figure 1) Suggested Reflow Profile

TAPE DIMENSIONS (mm)



A	B	C	D	F	J	L	M	Reel Dia.	Qty/Reel
3.5	2.8	8.0	3.5	4.0	1.1	0.25	1.0	180	1000

Figure 2) Pocket Tape Dimensions

Package Data	
Item	**Description**
Lid	Metal
Base	Ceramic
Sealing	Seam
Terminal	Tungsten (metalized)
Plating	Gold/Nickel (Surface)/(Under)
RoHS	Compliant (Pb Free)

1105 South Ridgeview Road • Olathe, KS 66062 • Phone: 913.782.7787 • Fax: 913.782.6991 • www.ecsxtal.com

ООО «НИОКРсистемс» - это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

Наша компания это:

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование
- Работаем по 275 ФЗ

ООО «НИОКР СИТЕМС»
Москва, 125362, Россия, ул. Вишневая, д. 9, к. 1, Блок 104 а и 104 в

Телефон: 8 (495) 268-14-82
Email: n@nsistems.ru

ИНН: 7735154786
ОГРН: 1167746717709