



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

## Internet Office 120V 700VA 425W Standby UPS, USB port, 6 Outlets, Tel/DSL/Ethernet Protection

MODEL NUMBER: **INTERNETOFFICE700**



### Description

Tripp Lite's INTERNETOFFICE700 standby UPS system offers surge suppression and long-lasting battery support for personal computers, internetworking equipment and other sensitive electronics. Internal UPS circuits support entry-level PC systems for up to 45 minutes during power failures and brownouts so that connected equipment can be shut down without data loss. Offers complete desktop power protection in an attractive gray tower configuration. Includes 3 battery-supported outlets for computer, monitor and one vital system peripheral, plus 3 additional surge suppression-only outlets for printers and other system accessories not requiring battery support. HID-compliant USB port enables optional unattended system shutdown without data loss in the case of extended power failure; USB cable included. HID compliant USB port enables integration with built-in power management and auto shutdown features of Windows and Mac OS X. PowerAlert software available via FREE download. Built-in RJ45 TEL/Ethernet suppression jacks protect modem, fax machine, cordless phone or other peripheral with a standard single-line tel/DSL or data line connection. Built-in audible alarm and 3 front panel LEDs indicate line power status, battery power status and battery low/replace status. 700VA/425W power handling ability supports entry-level PCs, network workstations, point-of-sale equipment, small business phone systems, audio/video equipment and home theater systems. Offers 3.9 min. battery runtime with a full load of 700VA and 11.2 min. with a half load of 350VA. Supports user battery replacement via built-in access panel. \$150,000 connected equipment insurance (USA and Canada Only).

### Features

- INTERNETOFFICE700 standby UPS system offers UPS battery support, plus complete AC and tel/Ethernet line surge suppression
- Supports entry-level PC systems for up to 45 min. during brownouts and power failures to enable a safe system shutdown
- Supports a max load of 700VA/425W for 3.9 min.

### Highlights

- 700VA tower 120V standby UPS
- Maintains AC output during power failures
- 3 UPS battery supported outlets, 3 surge-only outlets
- USB port, TEL/DSL/ethernet protection
- NEMA 5-15P input plug and 6 NEMA 5-15R outlets

### Package Includes

- INTERNETOFFICE700 UPS System
- USB cable
- Phone cable
- Instruction manual



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

- Supports a half load of 350VA/215W for 11.2 min.
- Supplies battery-derived AC output during brownouts starting at 99V, user adjustment allows fine tuning of brownout response to any setting from 83V to 99V
- Attractive gray tower configuration
- Includes 3 battery-supported outlets plus 3 additional surge suppression-only outlets, and 6-ft. AC line cord (all NEMA 5-15)
- USB port enables data-saving unattended shutdown when used with Tripp Lite's PowerAlert software, available via FREE download from [www.tripplite.com/poweralert](http://www.tripplite.com/poweralert)
- HID-compliant USB port enables integration with built-in power management and auto shutdown features of Windows and Mac OS X
- Supports Tripp Lite's WatchDog software application to restore unresponsive programs by automatically restarting them, and rebooting completely locked computers by automatically switching UPS power off and back on again
- Built-in phone/Ethernet suppression jacks protect modem, fax machine or other peripheral with a dialup, DSL, or data line connection
- Built-in audible alarm and 3 front panel LEDs indicate line power, battery power and battery low/replace status
- 700VA/425W power handling ability supports a variety of computer, internetworking, telecom and consumer electronics equipment
- Supports hot-swap battery replacement via built-in access panel
- Optional PDUB15 bypass PDU enables hot-swappable UPS replacement with no disruption to connected equipment
- Compatible with 120V/60Hz applications for USA, Canada, Mexico and more
- \$150,000 connected equipment insurance (USA and Canada Only)

## Specifications

| OVERVIEW                           |                     |
|------------------------------------|---------------------|
| UPC Code                           | 037332033284        |
| UPS Type                           | Standby             |
| INPUT                              |                     |
| Rated input current (Maximum Load) | 12A                 |
| Nominal Input Voltage(s) Supported | 120V AC             |
| UPS Input Connection Type          | 5-15P; Right-Angled |
| UPS Input Cord Length (ft.)        | 6                   |
| UPS Input Cord Length (m)          | 1.8                 |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

|                                                 |                                                                                                                                                                        |
|-------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Recommended Electrical Service                  | 15A 120V                                                                                                                                                               |
| Input Phase                                     | Single-Phase                                                                                                                                                           |
| <b>OUTPUT</b>                                   |                                                                                                                                                                        |
| Output Volt Amp Capacity (VA)                   | 700                                                                                                                                                                    |
| Output Watt Capacity (Watts)                    | 425                                                                                                                                                                    |
| Nominal Voltage Details                         | 115v nominal output in battery mode                                                                                                                                    |
| Frequency Compatibility                         | 60 Hz                                                                                                                                                                  |
| Output Voltage Regulation (Battery Mode)        | +/- 5%                                                                                                                                                                 |
| UPS Output Receptacles (Surge Suppression Only) | 3 UPS outlets, 3 surge-only outlets                                                                                                                                    |
| Hot-Swap PDU options                            | PDUB15 (2U / 8 5-15R outlets)                                                                                                                                          |
| Output AC Waveform (AC Mode)                    | Sine wave                                                                                                                                                              |
| Output AC Waveform (Battery Mode)               | PWM sine wave                                                                                                                                                          |
| Nominal Output Voltage(s) Supported             | 110V; 115V; 120V                                                                                                                                                       |
| Output Receptacles                              | (6) 5-15R                                                                                                                                                              |
| Individually Controllable Load Banks            | No                                                                                                                                                                     |
| <b>BATTERY</b>                                  |                                                                                                                                                                        |
| Full Load Runtime (min.)                        | 3.9 min. (425w)                                                                                                                                                        |
| Half Load Runtime (min.)                        | 11.2 min. (215w)                                                                                                                                                       |
| DC System Voltage (VDC)                         | 12                                                                                                                                                                     |
| Internal UPS Replacement Battery Cartridge      | &nbsp;<a class="productLink" href="//www.tripplite.com/UPS-Replacement-Battery-Cartridge-Tripp-Lite-APC-Belkin-Best-Powerware-Liebert-other-UPS~RBC51">RBC51</a>&nbsp; |
| Battery Access                                  | Battery access door                                                                                                                                                    |
| Battery Replacement Description                 | Hot-swappable, user replaceable batteries                                                                                                                              |
| Expandable Runtime                              | No                                                                                                                                                                     |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b>    |                                                                                                                                                                        |
| Switches                                        | 2 Switches control off/on power status and alarm-cancel/self-test operation                                                                                            |
| Alarm Cancel Operation                          | Power-fail alarm can be silenced using alarm-cancel switch; once silenced, alarm will re-sound to indicate low-battery status                                          |
| Audible Alarm                                   | Audible alarm indicates power-failure and low-battery conditions                                                                                                       |
| LED Indicators                                  | 3 LEDs indicate line power, battery power and battery low/replace status                                                                                               |
| <b>SURGE / NOISE SUPPRESSION</b>                |                                                                                                                                                                        |
| UPS AC Suppression Joule Rating                 | 510                                                                                                                                                                    |

4 / 5



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

|                                                             |                                                                                                                                                                                                                                           |
|-------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WatchDog Compatibility                                      | Supports Watchdog application, OS and hard-reboot restart options for remote applications                                                                                                                                                 |
| Network UPS Tools Compatibility                             | NUT compatible. See the full list of Tripp Lite NUT compatible UPS systems at <a href="http://www.networkupstools.org/stable-hcl.html?manufacturer=Tripp+Lite">http://www.networkupstools.org/stable-hcl.html?manufacturer=Tripp Lite</a> |
| Communications Interface                                    | USB (HID enabled)                                                                                                                                                                                                                         |
| <b>LINE / BATTERY TRANSFER</b>                              |                                                                                                                                                                                                                                           |
| Transfer Time                                               | 2-4 milliseconds                                                                                                                                                                                                                          |
| Low Voltage Transfer to Battery Power (Setpoint)            | 99 (adjustable to 83 via back panel potentiometer)                                                                                                                                                                                        |
| High Voltage Transfer to Battery Power (Setpoint)           | 139                                                                                                                                                                                                                                       |
| <b>SPECIAL FEATURES</b>                                     |                                                                                                                                                                                                                                           |
| Cold Start (Startup in Battery Mode During a Power Failure) | Cold-start operation supported                                                                                                                                                                                                            |
| High Availability UPS Features                              | Hot swappable batteries                                                                                                                                                                                                                   |
| Green Energy-Saving Features                                | Greater than 95% efficiency - GREEN UPS                                                                                                                                                                                                   |
| <b>STANDARDS &amp; COMPLIANCE</b>                           |                                                                                                                                                                                                                                           |
| UPS Certifications                                          | Tested to UL1778 (USA); Tested to CSA (Canada); Tested to NOM (Mexico); Meets FCC Part 15 Category B (EMI)                                                                                                                                |
| <b>WARRANTY</b>                                             |                                                                                                                                                                                                                                           |
| Product Warranty Period (U.S. & Canada)                     | 3-year limited warranty                                                                                                                                                                                                                   |
| Product Warranty Period (Latin America)                     | 3-year limited warranty                                                                                                                                                                                                                   |
| Product Warranty Period (International)                     | 2-year limited warranty                                                                                                                                                                                                                   |
| Product Warranty Period (Mexico)                            | 3-year limited warranty                                                                                                                                                                                                                   |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico)  | \$150,000&nbsp;<a class="insuranceLink" href="//www.tripplite.com/support/insurance-policy">Ultimate Lifetime Insurance</a>&nbsp;                                                                                                         |

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>



**ООО «НИОКРсистемс»** - это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

### **Наша компания это:**

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование
- Работаем по 275 ФЗ