Bulletin PD-20057 01/01

International
IOR Rectifier

10TQ...
10TQ...S

SCHOTTKY RECTIFIER

10 Amp

$I_{F(AV)}$ = 10Amp
V_R = 35 to 45V

Major Ratings and Characteristics

Characteristics		10TQ	Units
$I_{F(AV)}$	Rectangular waveform	10	A
V_{RRM}		35 to 45	V
I_{FSM}	@ tp = 5 µs sine	1050	A
V_F	@ 10 Apk, T_J = 125°C	0.49	V
T_J	range	- 55 to 175	°C

Description/ Features

The 10TQ.. Schottky rectifier series has been optimized for low reverse leakage at high temperature. The proprietary barrier technology allows for reliable operation up to 175° C junction temperature. Typical applications are in switching power supplies, converters, free-wheeling diodes, and reverse battery protection.

- 175° C T_J operation
- High purity, high temperature epoxy encapsulation for enhanced mechanical strength and moisture resistance
- Low forward voltage drop
- High frequency operation
- Guard ring for enhanced ruggedness and long term reliability

Case Styles

10TQ...	10TQ... S
	
TO-220	D^2PAK

Voltage Ratings

	Part number	10TQ035	10TQ040	10TQ045
V_R	Max. DC Reverse Voltage (V)	35	40	45
V_{RWM}	Max. Working Peak Reverse Voltage (V)			

Absolute Maximum Ratings

	Parameters	10TQ	Units	Conditions	
$I_{F(AV)}$	Max. Average Forward Current * See Fig. 5	10	A	50% duty cycle @ T_C = 151° C, rectangular wave form	
I_{FSM}	Max. Peak One Cycle Non-Repetitive Surge Current * See Fig. 7	1050	A	5µs Sine or 3µs Rect. pulse	Following any rated load condition and with rated V_{RRM} applied
		280		10ms Sine or 6ms Rect. pulse	
E_{AS}	Non-Repetitive Avalanche Energy	13	mJ	T_J = 25 °C, I_{AS} = 2 Amps, L = 6.5 mH	
I_{AR}	Repetitive Avalanche Current	2	A	Current decaying linearly to zero in 1 µsec Frequency limited by T_J max. V_A = 1.5 x V_R typical	

Electrical Specifications

	Parameters	10TQ	Units	Conditions	
V_{FM}	Max. Forward Voltage Drop (1) * See Fig. 1	0.57	V	@ 10A	T_J = 25 °C
		0.67	V	@ 20A	
		0.49	V	@ 10A	T_J = 125 °C
		0.61	V	@ 20A	
I_{RM}	Max. Reverse Leakage Current (1) * See Fig. 2	2	mA	T_J = 25 °C	V_R = rated V_R
		15	mA	T_J = 125 °C	
C_T	Max. Junction Capacitance	900	pF	V_R = 5V_{DC}, (test signal range 100Khz to 1Mhz) 25 °C	
L_S	Typical Series Inductance	8.0	nH	Measured lead to lead 5mm from package body	
dv/dt	Max. Voltage Rate of Change (Rated V_R)	10,000	V/ µs		

(1) Pulse Width < 300µs, Duty Cycle < 2%

Thermal-Mechanical Specifications

	Parameters		10TQ	Units	Conditions
T_J	Max. Junction Temperature Range		-55 to 175	°C	
T_{stg}	Max. Storage Temperature Range		-55 to 175	°C	
R_{thJC}	Max. Thermal Resistance Junction to Case		2.0	°C/W	DC operation * See Fig. 4
R_{thCS}	Typical Thermal Resistance, Case to Heatsink		0.50	°C/W	Mounting surface , smooth and greased
wt	Approximate Weight		2 (0.07)	g (oz.)	
T	Mounting Torque	Min.	6 (5)	Kg-cm (lbf-in)	
		Max.	12 (10)		




Fig. 1 - Maximum Forward Voltage Drop Characteristics




Fig. 2 - Typical Values of Reverse Current Vs. Reverse Voltage




Fig. 3 - Typical Junction Capacitance Vs. Reverse Voltage




Fig. 4 - Maximum Thermal Impedance Z_{thJC} Characteristics




Fig. 5 - Maximum Allowable Case Temperature Vs. Average Forward Current




Fig. 6 - Forward Power Loss Characteristics




Fig. 7 - Maximum Non-Repetitive Surge Current






Fig. 8 - Unclamped Inductive Test Circuit

Outline Table




Conform to JEDEC outline TO-220AC
Dimensions in millimeters and (inches)



Conform to JEDEC outline D^2Pak (SMD-220)
Dimensions in millimeters and (inches)

Ordering Information Table

Device Code



1	-	Essential Part Number
2	-	T = TO-220
3	-	Q = Schottky Q Series
4	-	Voltage Rating
5	-	S = D^2Pak

- 035 = 35V
- 040 = 40V
- 045 = 45V

International
IOR Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105
TAC Fax: (310) 252-7309
Visit us at www.irf.com for sales contact information. 01/01

ООО «НИОКРсистемс» - это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

Наша компания это:

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование
- Работаем по 275 ФЗ

ООО «НИОКР СИТЕМС»
Москва, 125362, Россия, ул. Вишневая, д. 9, к. 1, Блок 104 а и 104 в

Телефон: 8 (495) 268-14-82
Email: n@nsistems.ru

ИНН: 7735154786
ОГРН: 1167746717709