




## Fast Avalanche Sinterglass Diode



### FEATURES

- Glass passivated junction
- Hermetically sealed package
- Low reverse current
- Soft recovery characteristics
- Material categorization:  
For definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)



**RoHS**  
COMPLIANT  
HALOGEN  
**FREE**

### MECHANICAL DATA

**Case:** SOD-64

**Terminals:** plated axial leads, solderable per MIL-STD-750, method 2026

**Polarity:** color band denotes cathode end

**Mounting position:** any

**Weight:** approx. 858 mg

### APPLICATIONS

- Very fast rectification and switching diode

### ORDERING INFORMATION (Example)

| DEVICE NAME | ORDERING CODE | TAPED UNITS                | MINIMUM ORDER QUANTITY |
|-------------|---------------|----------------------------|------------------------|
| BYT56M      | BYT56M-TR     | 2500 per 10" tape and reel | 12 500                 |
| BYT56M      | BYT56M-TAP    | 2500 per ammpack           | 12 500                 |

### PARTS TABLE

| PART   | TYPE DIFFERENTIATION                             | PACKAGE |
|--------|--------------------------------------------------|---------|
| BYT56A | $V_R = 50\text{ V}$ ; $I_{F(AV)} = 3\text{ A}$   | SOD-64  |
| BYT56B | $V_R = 100\text{ V}$ ; $I_{F(AV)} = 3\text{ A}$  | SOD-64  |
| BYT56D | $V_R = 200\text{ V}$ ; $I_{F(AV)} = 3\text{ A}$  | SOD-64  |
| BYT56G | $V_R = 400\text{ V}$ ; $I_{F(AV)} = 3\text{ A}$  | SOD-64  |
| BYT56J | $V_R = 600\text{ V}$ ; $I_{F(AV)} = 3\text{ A}$  | SOD-64  |
| BYT56K | $V_R = 800\text{ V}$ ; $I_{F(AV)} = 3\text{ A}$  | SOD-64  |
| BYT56M | $V_R = 1000\text{ V}$ ; $I_{F(AV)} = 3\text{ A}$ | SOD-64  |

### ABSOLUTE MAXIMUM RATINGS ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)

| PARAMETER                                         | TEST CONDITION                        | PART   | SYMBOL          | VALUE         | UNIT               |
|---------------------------------------------------|---------------------------------------|--------|-----------------|---------------|--------------------|
| Reverse voltage = repetitive peak reverse voltage | See electrical characteristics        | BYT56A | $V_R = V_{RRM}$ | 50            | V                  |
|                                                   |                                       | BYT56B | $V_R = V_{RRM}$ | 100           | V                  |
|                                                   |                                       | BYT56D | $V_R = V_{RRM}$ | 200           | V                  |
|                                                   |                                       | BYT56G | $V_R = V_{RRM}$ | 400           | V                  |
|                                                   |                                       | BYT56J | $V_R = V_{RRM}$ | 600           | V                  |
|                                                   |                                       | BYT56K | $V_R = V_{RRM}$ | 800           | V                  |
|                                                   |                                       | BYT56M | $V_R = V_{RRM}$ | 1000          | V                  |
| Peak forward surge current                        | $t_p = 10\text{ ms}$ , half sine wave |        | $I_{FSM}$       | 80            | A                  |
| Average forward current                           | On PC board                           |        | $I_{F(AV)}$     | 1.5           | A                  |
|                                                   | $l = 10\text{ mm}$                    |        | $I_{F(AV)}$     | 3             | A                  |
| Non repetitive reverse avalanche energy           | $I_{(BR)R} = 0.4\text{ A}$            |        | $E_R$           | 10            | mJ                 |
| Junction and storage temperature range            |                                       |        | $T_J = T_{stg}$ | - 55 to + 175 | $^{\circ}\text{C}$ |

### MAXIMUM THERMAL RESISTANCE ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)

| PARAMETER        | TEST CONDITION                                           | SYMBOL     | VALUE | UNIT |
|------------------|----------------------------------------------------------|------------|-------|------|
| Junction ambient | Lead length $l = 10\text{ mm}$ , $T_L = \text{constant}$ | $R_{thJA}$ | 25    | K/W  |
|                  | On PC board with spacing 25 mm                           | $R_{thJA}$ | 70    | K/W  |



## ELECTRICAL CHARACTERISTICS ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)

| PARAMETER             | TEST CONDITION                                              | PART | SYMBOL   | MIN. | TYP. | MAX. | UNIT          |
|-----------------------|-------------------------------------------------------------|------|----------|------|------|------|---------------|
| Forward voltage       | $I_F = 3\text{ A}$                                          |      | $V_F$    | -    | -    | 1.4  | V             |
| Reverse current       | $V_R = V_{RRM}$                                             |      | $I_R$    | -    | -    | 5    | $\mu\text{A}$ |
|                       | $V_R = V_{RRM}, T_J = 150\text{ }^{\circ}\text{C}$          |      | $I_R$    | -    | -    | 150  | $\mu\text{A}$ |
| Reverse recovery time | $I_F = 0.5\text{ A}, I_R = 1\text{ A}, i_R = 0.25\text{ A}$ |      | $t_{rr}$ | -    | -    | 100  | ns            |

## TYPICAL CHARACTERISTICS ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)




Fig. 1 - Max. Thermal Resistance vs. Lead Length




Fig. 3 - Max. Average Forward Current vs. Ambient Temperature




Fig. 2 - Max. Forward Current vs. Forward Voltage




Fig. 4 - Max. Reverse Current vs. Junction Temperature




Fig. 5 - Max. Reverse Power Dissipation vs. Junction Temperature





Fig. 6 - Diode Capacitance vs. Reverse Voltage

## PACKAGE DIMENSIONS in millimeters (inches): SOD-64



Document-No.: 6.563-5006.4-4  
Rev. 3 - Date: 09.February.2005  
94 9587



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.**



**ООО «НИОКРсистемс»** - это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

### **Наша компания это:**

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование
- Работаем по 275 ФЗ