
## OFCBU/OFCBUGB


**Optical Fiber Tube Gripper Saddle**





### Features

- Cable retention: >1.5kN
- OFBLT retention: >100N
- Maximum of 24 cable elements or 24 fiber bundles




| Gland Box Part No. | Cable Diameter |
|---|---|
| OFCBUGB-00 | .16-.33 (4.0 - 8.5) |
| OFCBUGB-0 | .30-.79 (7.5 - 20.0) |
| OFCBUGB-1 | .37-.51 (9.5 - 13.0) |
| OFCBUGB-2 | .51-.71 (13.0 - 18.0) |
| OFCBUGB-3 | .69-.98 (17.5 - 25.0) |
| Standard Pack: 1 per bag | |

### Description

At distribution points, multi-fiber cables need to have the individual fibers or cable elements separated and protected by a management system.

The cable strength member has to be terminated and anchored to prevent damage to the fibers from cable movement or pull out.

The Optical Fiber Cable Breakout Unit affords quick, easy and positive arrangements of the fibers or cable elements, which are sheathed in OFBLT to give permanent protection. Assembly of tubes is made easy by a simple “lay through” design, no threading is required.

The strength member retainer is simply inserted over the terminated cable as shown and clamps both the cable and the breakout unit to the jointing chassis.


A secure fiber management system that minimizes installation time and maximizes fiber integrity and security. Once installed, it can be left with total peace of mind.

For further protection, a gland box is available.

| Miniflex technology manufactured by Richco - Patented | | | | | | | |
|---|---|---|---|---|---|---|---|
| Material: Flame Retardant Nylon, RMS-19 (UL 94V0); Bolt: Stainless Steel • Color: Black | | | | | | | |
| Part No. | Standard Pack: 10/bag | | | | | | |
| | “d1” | “d2” | “D” | “H” | “L” | “X” | “Y” |
| OFCBU-24-05-19BLK | .20 (5.0) | .19 (4.7) | 1.73 (44.0) | .63 (16.0) | 1.93 (49.0) | 1.73 (44.0) | .31 (8.0) |

## OFM


**Optical Fiber Manifold**





### Features

- Ability to stack
- Tube retention: >100N
- For OFM Crimp Rings (For terminating GRP strength members) order: OFM-CR
- For a Development Kit containing all adapters, order: OFM-4-05-19BLK
- Gland box also available (see above picture); use part number: OFM-04-PG16BLK




### Description

The 1 into 4 Optical Fiber Manifold enables small multiple fiber cables with aramid and similar strength reinforcement or central GRP strength member to be mechanically and securely terminated. OFBLT at the output ports gives full radius control and crush protection while still allowing an easy to route fiber “lay-through” design. OFBLT can also be used at the input port

| Part No. | “ D” | “h” | “A” | “d” | “H” | “L” | “W” |
|---|---|---|---|---|---|---|---|
| OFM series | .51 (13.0) | 1.14 (29.0) | .73 (18.5) | .20 (5.0) | 1.87 (47.5) | 0.91 (23.0) | 0.91 (23.0) |

| Miniflex technology manufactured by Richco - Patented | | |
|---|---|---|
| Material: Flame Retardant Nylon, RMS-19 (UL 94V0); Color Black | | |
| Part No. | Standard Pack: 10/bag | |
| | Incoming Cable Size Diameter | Adapter Color |
| OFM-C-1-05-19BLK | .098 - .138 (2.5 - 3.5) | Black |
| OFM-C-2-05-19BLK | .118 - .157 (3.0 - 4.0) | Blue |
| OFM-C-3-05-19BLK | .161 - .197 (4.1 - 5.0) | Brown |
| OFM-C-4-05-19BLK | .201 - .236 (5.1 - 6.0) | Green |
| OFM-C-5-05-19BLK | .240 - .276 (6.1 - 7.0) | Red |
| OFM-C-6-05-19BLK | .280 - .335 (7.1 - 8.5) | Black Rubber |
| OFM-C-7-05-19BLK | .335 - .425 (8.5 - 10.8) | Black Rubber |
| OFM-T-05-19BLK | .197 (5.0) OFBLT | Split Black |
| OFM-T-635-19BLK | .197 - .250 (5.0 - 6.35) OFBLT | Split Blue |

J

**ООО «НИОКРсистемс» -** это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

## Наша компания это:

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование
- Работаем по 275 ФЗ

ООО «НИОКР СИТЕМС»
Москва, 125362, Россия, ул. Вишневая, д. 9, к. 1, Блок 104 а и 104 в

Телефон: 8 (495) 268-14-82
Email: n@nsistems.ru

ИНН: 7735154786
ОГРН: 1167746717709