

# FDS7064A

## 30V N-Channel PowerTrench<sup>®</sup> MOSFET

### General Description



This N-Channel MOSFET has been designed specifically to improve the overall efficiency of DC/DC converters using either synchronous or conventional switching PWM controllers. It has been optimized for "low side" synchronous rectifier operation, providing an extremely low  $R_{DS(ON)}$  in a small package.

### Applications

- Synchronous rectifier
- DC/DC converter

### Features

- 19 A, 30 V  $R_{DS(ON)} = 6.5 \text{ m}\Omega @ V_{GS} = 4.5 \text{ V}$
- High performance trench technology for extremely low  $R_{DS(ON)}$
- High power and current handling capability
- Fast switching
- Bottomless™ SO-8 package: Enhanced thermal performance in industry-standard package size



### Absolute Maximum Ratings $T_A=25^\circ\text{C}$ unless otherwise noted

| Symbol         | Parameter  | Ratings     | Units            |
|----------------|--|-------------|------------------|
| $V_{DSS}$      | Drain-Source Voltage                             | 30          | V                |
| $V_{GSS}$      | Gate-Source Voltage                              | $\pm 12$    | V                |
| $I_D$          | Drain Current – Continuous (Note 1a)             | 19          | A                |
|                | – Pulsed   | 60          |                  |
| $P_D$          | Power Dissipation for Single Operation (Note 1a) | 3.9         | W                |
| $T_J, T_{STG}$ | Operating and Storage Junction Temperature Range | -55 to +175 | $^\circ\text{C}$ |

### Thermal Characteristics

|                 |   |    |                    |
|-----------------|---|----|--------------------|
| $R_{\theta JA}$ | Thermal Resistance, Junction-to-Ambient (Note 1a) | 38 | $^\circ\text{C/W}$ |
| $R_{\theta JC}$ | Thermal Resistance, Junction-to-Case              | 1  | $^\circ\text{C/W}$ |

### Package Marking and Ordering Information

| Device Marking | Device   | Reel Size | Tape width | Quantity   |
|----------------|----------|-----------|------------|------------|
| FDS7064A       | FDS7064A | 13"       | 12mm       | 2500 units |

**Electrical Characteristics** $T_A = 25^\circ\text{C}$  unless otherwise noted

| Symbol | Parameter | Test Conditions | Min | Typ | Max | Units |
|--------|-----------|-----------------|-----|-----|-----|-------|
|--------|-----------|-----------------|-----|-----|-----|-------|

**Off Characteristics**

|                                      |   |   |    |    |      |               |
|--------------------------------------|---|---|----|----|------|---------------|
| $BV_{DSS}$                           | Drain–Source Breakdown Voltage            | $V_{GS} = 0\text{ V}, I_D = 250\ \mu\text{A}$               | 30 |    |      | V             |
| $\frac{\Delta BV_{DSS}}{\Delta T_J}$ | Breakdown Voltage Temperature Coefficient | $I_D = 250\ \mu\text{A}$ , Referenced to $25^\circ\text{C}$ |    | 20 |      | mV/°C         |
| $I_{DSS}$                            | Zero Gate Voltage Drain Current           | $V_{DS} = 24\text{ V}, V_{GS} = 0\text{ V}$                 |    |    | 1    | $\mu\text{A}$ |
| $I_{GSSF}$                           | Gate–Body Leakage, Forward                | $V_{GS} = 12\text{ V}, V_{DS} = 0\text{ V}$                 |    |    | 100  | nA            |
| $I_{GSSR}$                           | Gate–Body Leakage, Reverse                | $V_{GS} = -12\text{ V}, V_{DS} = 0\text{ V}$                |    |    | -100 | nA            |

**On Characteristics** (Note 2)

|  |  |   |     |     |            |            |
|--|--|---|-----|-----|------------|------------|
| $V_{GS(th)}$                           | Gate Threshold Voltage                         | $V_{DS} = V_{GS}, I_D = 250\ \mu\text{A}$   | 0.8 | 1.2 | 2          | V          |
| $\frac{\Delta V_{GS(th)}}{\Delta T_J}$ | Gate Threshold Voltage Temperature Coefficient | $I_D = 250\ \mu\text{A}$ , Referenced to $25^\circ\text{C}$                             |     | -4  |            | mV/°C      |
| $R_{DS(on)}$                           | Static Drain–Source On–Resistance              | $V_{GS} = 4.5\text{ V}, I_D = 19\text{ A}$<br>$V_{GS} = 10\text{ V}, I_D = 21\text{ A}$ |     |     | 6.5<br>5.5 | m $\Omega$ |
| $I_{D(on)}$                            | On–State Drain Current                         | $V_{GS} = 4.5\text{ V}, V_{DS} = 5\text{ V}$  | 50  |     |            | A          |
| $g_{FS}$                               | Forward Transconductance                       | $V_{DS} = 10\text{ V}, I_D = 19\text{ A}$   |     | 75  |            | S          |

**Dynamic Characteristics**

|           |                              |  |  |      |  |    |
|-----------|------------------------------|--|--|------|--|----|
| $C_{iss}$ | Input Capacitance            | $V_{DS} = 15\text{ V}, V_{GS} = 0\text{ V},$<br>$f = 1.0\text{ MHz}$ |  | 5070 |  | pF |
| $C_{oss}$ | Output Capacitance           |  |  | 550  |  | pF |
| $C_{rss}$ | Reverse Transfer Capacitance |  |  | 230  |  | pF |

**Switching Characteristics** (Note 2)

|              |                     |   |  |     |     |    |
|--------------|---------------------|---|--|-----|-----|----|
| $t_{d(on)}$  | Turn–On Delay Time  | $V_{DD} = 10\text{ V}, I_D = 1\text{ A},$<br>$V_{GS} = 4.5\text{ V}, R_{GEN} = 6\ \Omega$ |  | 17  | 25  | ns |
| $t_r$        | Turn–On Rise Time   |   |  | 18  | 25  | ns |
| $t_{d(off)}$ | Turn–Off Delay Time |   |  | 69  | 100 | ns |
| $t_f$        | Turn–Off Fall Time  |   |  | 29  | 42  | ns |
| $Q_g$        | Total Gate Charge   | $V_{DS} = 15\text{ V}, I_D = 19\text{ A},$<br>$V_{GS} = 4.5\text{ V}$                     |  | 33  | 46  | nC |
| $Q_{gs}$     | Gate–Source Charge  |   |  | 7.5 |     | nC |
| $Q_{gd}$     | Gate–Drain Charge   |   |  | 6.8 |     | nC |

**Drain–Source Diode Characteristics and Maximum Ratings**


|          |   |  |  |  |     |   |
|----------|---|--|--|--|-----|---|
| $I_S$    | Maximum Continuous Drain–Source Diode Forward Current |  |  |  | 3.2 | A |
| $V_{SD}$ | Drain–Source Diode Forward Voltage                    | $V_{GS} = 0\text{ V}, I_S = 3.2\text{ A}$ (Note 2) |  |  | 1.2 | V |

**Notes:**


1.  $R_{\theta JA}$  is the junction-to-ambient thermal resistance.  $R_{\theta JA}$  depends on the user's board design.

- a)  $38^\circ\text{C/W}$  when mounted on a  $1\text{ in}^2$  pad of 2 oz copper





**Dimensional Outline and Pad Layout**



**Bottom View**



**Top View**



**Minimum Recommended Landing Pattern**

**Notes** Unless otherwise Specified

- a) All dimensions in mm
- b) Standard lead finish:  
20 – 80 μ inches nickel /  
6 μ inches palladium
- c) Chip Size Dimensional Table

| Chip Size |      | X2   | Y2   |
|-----------|------|------|------|
| X1        | Y1   |      |      |
| 2.36      | 2.36 | 0.75 | 0.67 |

## TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

|                      |               |             |
|----------------------|---------------|-------------|
| ACEx™                | HiSeC™        | SuperSOT™-8 |
| Bottomless™          | ISOPLANAR™    | SyncFET™    |
| CoolFET™             | MICROWIRE™    | TinyLogic™  |
| CROSSVOLT™           | POP™          | UHC™        |
| E <sup>2</sup> CMOS™ | PowerTrench®  | VCX™        |
| FACT™                | QFET™         |             |
| FACT Quiet Series™   | QS™           |             |
| FAST®                | Quiet Series™ |             |
| FASTr™               | SuperSOT™-3   |             |
| GTO™                 | SuperSOT™-6   |             |

## DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

## LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

## PRODUCT STATUS DEFINITIONS

### Definition of Terms

| Datasheet Identification | Product Status         | Definition  |
|--------------------------|------------------------|---|
| Advance Information      | Formative or In Design | This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.  |
| Preliminary              | First Production       | This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design. |
| No Identification Needed | Full Production        | This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.   |
| Obsolete                 | Not In Production      | This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.   |



**ООО «НИОКРсистемс»** - это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

### **Наша компания это:**

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование
- Работаем по 275 ФЗ