


GORDOS

REED RELAYS


83 SERIES MOLDED DIP THRU-HOLE AND SURFACE MOUNT DRY REED RELAYS



FEATURES:


- Choice of Gull or J-Lead Surface Mount or Thru-hole Configuration
- Surface Mount Versions Pass High Reliability Steam Aging Solderability Test
- Surface Mount Versions Compatible with IR Reflow Systems
- 94V-O Flammability Rating
- Form A, 2A, B or C Contacts
- Logic Compatible 5, 12 or 24 Volt Operation
- Available with or without Diodes
- Compatible with Automatic Insertion
- Semiconductor Grade Molding Compounds
- -20° C to 85° C Operating,
-20° C to 100° C Storage Temperature Ranges

THRU-HOLE




(DIMENSIONAL TOL. $\pm .010''$ TYP.)

THRU-HOLE



GULL LEAD



"J" LEAD

Products and specifications subject to change without notice.
Consult factory for application assistance.

1000 N. SECOND ST., ROGERS, AR 72756 USA / TEL: 800-643-3500 / 501-636-5000 / FAX: 501-636-2305

GORDOS

REED RELAYS

83 SERIES MOLDED DIP THRU-HOLE AND SURFACE MOUNT DRY REED RELAYS

Nominal Coil Voltage DC	5	12	24
Must Operate Voltage DC	3.8	9.0	18.0
Must Release Voltage DC	0.5	1.2	2.4
Maximum Voltage DC (3)	10	20	35

Contact Arrangement		1 Form-A		(3) Form-B	Form-C		
Model Type		831A	832A	831B	831C	835C	836C
Max. Switching DC ⁽²⁾	Watts	10		10		3	
	Volts	200		200		30	
Max. Current DC (amps)	Switch	0.5		0.5		0.2	
	Carry	1.5		1.5		0.5	
Max. Initial Contact Resistance (ohms) ⁽¹⁾		0.200		0.200		0.200	
Min. Breakdown Voltage DC	Across Contacts	250		250		200	
	Contact to Coil	750		750		750	
Capacitance (typical) pF	Across Contacts	1.0		—		1.5	
	Contact to Coil	2.0		3.8		2.0	
Insulation Resistance (typical ohms)		10 ¹⁰		10 ¹⁰		10 ⁸	
Operate Time (typical mSec) Including Bounce Except Form-B		0.5		0.5		1.0	
Release Time (typical mSec) Diode Suppressed		0.5		0.5		1.5 includes Bounce on N.C. Pole	

REED RELAY SELECTION CHART *Shading denotes shortest lead time items.*

SERIES 47 MINI-SIP

Contact Arrangement	Nominal Coil Voltage (VDC)	Coil Resistance (ohms) ± 10% @ 25° C	Suppression Diode	Catalog Number			Schematics (Top View)
				Thru-Hole	Gull-Lead	J-Lead	
1A SPST N.O.	5	380	No	831A-1	831A-1G	831A-1J	
		500	No	831A-3	831A-3G	831A-3J	
	12	1000	No	831A-5	831A-5G	831A-5J	
	24	1750	No	831A-7	831A-7G	831A-7J	
1B (See Note 3) SPST N.C.	5	200	No	831B-1	831B-1G	831B-1J	
		500	No	831B-3	831B-3G	831B-3J	
	12	500	No	831B-5	831B-5G	831B-5J	
	24	1750	No	831B-7	831B-7G	831B-7J	
1C SPDT	5	200	No	831C-1	831C-1G	831C-1J	
		500	No	831C-3	831C-3G	831C-3J	
	12	500	No	831C-5	831C-5G	831C-5J	
	24	1750	No	831C-6	831C-6G	831C-6J	
1C SPDT	5	200	No	835C-1	835C-1G	835C-1J	
		500	No	835C-3	835C-3G	835C-3J	
	12	500	No	835C-5	835C-5G	83	



ООО «НИОКРсистемс» - это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

Наша компания это:

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование
- Работаем по 275 ФЗ