

# FDD6676

## 30V N-Channel PowerTrench® MOSFET

### General Description



This N-Channel MOSFET has been designed specifically to improve the overall efficiency of DC/DC converters using either synchronous or conventional switching PWM controllers. It has been optimized for low gate charge, low  $R_{DS(ON)}$  and fast switching speed. extremely low  $R_{DS(ON)}$  in a small package.

### Applications

- DC/DC converter
- Motor Drives

### Features

- 78 A, 30 V  $R_{DS(ON)} = 7.5 \text{ m}\Omega @ V_{GS} = 10 \text{ V}$   
 $R_{DS(ON)} = 8.5 \text{ m}\Omega @ V_{GS} = 4.5 \text{ V}$
- Low gate charge
- Fast Switching
- High performance trench technology for extremely low  $R_{DS(ON)}$



### Absolute Maximum Ratings T<sub>A</sub>=25°C unless otherwise noted

| Symbol                            | Parameter                                        | Ratings     | Units |
|-----------------------------------|--------------------------------------------------|-------------|-------|
| V <sub>DSS</sub>                  | Drain-Source Voltage                             | 30          | V     |
| V <sub>GSS</sub>                  | Gate-Source Voltage                              | ±16         | V     |
| I <sub>D</sub>                    | Drain Current – Continuous (Note 3)              | 78          | A     |
|                                   | – Pulsed (Note 1a)                               | 100         |       |
| P <sub>D</sub>                    | Power Dissipation for Single Operation (Note 1)  | 83          | W     |
|                                   | (Note 1a)                                        | 3.8         |       |
|                                   | (Note 1b)                                        | 1.6         |       |
| T <sub>J</sub> , T <sub>STG</sub> | Operating and Storage Junction Temperature Range | -55 to +175 | °C    |

### Thermal Characteristics

|                  |                                                   |     |      |
|------------------|---------------------------------------------------|-----|------|
| R <sub>θJC</sub> | Thermal Resistance, Junction-to-Case (Note 1)     | 1.8 | °C/W |
| R <sub>θJA</sub> | Thermal Resistance, Junction-to-Ambient (Note 1a) | 40  | °C/W |
| R <sub>θJA</sub> | Thermal Resistance, Junction-to-Ambient (Note 1b) | 96  | °C/W |

### Package Marking and Ordering Information

| Device Marking | Device  | Reel Size | Tape width | Quantity   |
|----------------|---------|-----------|------------|------------|
| FDD6676        | FDD6676 | 13"       | 12mm       | 2500 units |

**Electrical Characteristics** $T_A = 25^\circ\text{C}$  unless otherwise noted

| Symbol                                  | Parameter                                      | Test Conditions                                                                                                                                                              | Min | Typ               | Max                | Units |
|-----------------------------------------|------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|-------------------|--------------------|-------|
| Drain-Source Avalanche Ratings (Note 2) |                                                |                                                                                                                                                                              |     |                   |                    |       |
| W <sub>DSS</sub>                        | Drain-Source Avalanche Energy                  | Single Pulse, V <sub>DD</sub> = 15 V, I <sub>D</sub> =21A                                                                                                                    |     |                   | 370                | mJ    |
| I <sub>AR</sub>                         | Drain-Source Avalanche Current                 |                                                                                                                                                                              |     |                   | 21                 | A     |
| Off Characteristics                     |                                                |                                                                                                                                                                              |     |                   |                    |       |
| BV <sub>DSS</sub>                       | Drain–Source Breakdown Voltage                 | V <sub>GS</sub> = 0 V, I <sub>D</sub> = 250 μA                                                                                                                               | 30  |                   |                    | V     |
| $\frac{\Delta BV_{DSS}}{\Delta T_J}$    | Breakdown Voltage Temperature Coefficient      | I <sub>D</sub> = 250 μA,Referenced to 25°C                                                                                                                                   |     | 24                |                    | mV/°C |
| I <sub>DSS</sub>                        | Zero Gate Voltage Drain Current                | V <sub>DS</sub> = 24 V,    V <sub>GS</sub> = 0 V                                                                                                                             |     |                   | 1                  | μA    |
| I <sub>GSSF</sub>                       | Gate–Body Leakage, Forward                     | V <sub>GS</sub> = 16 V,    V <sub>DS</sub> = 0 V                                                                                                                             |     |                   | 100                | nA    |
| I <sub>GSSR</sub>                       | Gate–Body Leakage, Reverse                     | V <sub>GS</sub> = –16 V    V <sub>DS</sub> = 0 V                                                                                                                             |     |                   | –100               | nA    |
| On Characteristics (Note 2)             |                                                |                                                                                                                                                                              |     |                   |                    |       |
| V <sub>GS(th)</sub>                     | Gate Threshold Voltage                         | V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = 250 μA                                                                                                                  | 1   | 1.5               | 3                  | V     |
| $\frac{\Delta V_{GS(th)}}{\Delta T_J}$  | Gate Threshold Voltage Temperature Coefficient | I <sub>D</sub> = 250 μA,Referenced to 25°C                                                                                                                                   |     | -5                |                    | mV/°C |
| R <sub>DS(on)</sub>                     | Static Drain–Source On–Resistance              | V <sub>GS</sub> = 10 V, I <sub>D</sub> = 16.8 A<br>V <sub>GS</sub> = 4.5 V, I <sub>D</sub> = 15.8 A<br>V <sub>GS</sub> = 10 V, I <sub>D</sub> = 16.8 A,T <sub>J</sub> =125°C |     | 4.8<br>5.4<br>7.3 | 7.5<br>8.5<br>10.5 | mΩ    |
| I <sub>D(on)</sub>                      | On–State Drain Current                         | V <sub>GS</sub> = 10 V,    V <sub>DS</sub> = 5 V                                                                                                                             | 50  |                   |                    | A     |
| g <sub>FS</sub>                         | Forward Transconductance                       | V <sub>DS</sub> = 5 V,    I <sub>D</sub> = 16.8 A                                                                                                                            |     | 80                |                    | S     |
| Dynamic Characteristics                 |                                                |                                                                                                                                                                              |     |                   |                    |       |
| C <sub>iss</sub>                        | Input Capacitance                              | V <sub>DS</sub> = 15 V,    V <sub>GS</sub> = 0 V,<br>f = 1.0 MHz                                                                                                             |     | 5103              |                    | pF    |
| C <sub>oss</sub>                        | Output Capacitance                             |                                                                                                                                                                              |     | 836               |                    | pF    |
| C <sub>rss</sub>                        | Reverse Transfer Capacitance                   |                                                                                                                                                                              |     | 361               |                    | pF    |
| Switching Characteristics (Note 2)      |                                                |                                                                                                                                                                              |     |                   |                    |       |
| t <sub>d(on)</sub>                      | Turn–On Delay Time                             | V <sub>DD</sub> = 15 V,    I <sub>D</sub> = 1 A,<br>V <sub>GS</sub> = 10 V,    R <sub>GEN</sub> = 6 Ω                                                                        |     | 15                | 27                 | ns    |
| t <sub>r</sub>                          | Turn–On Rise Time                              |                                                                                                                                                                              |     | 9                 | 18                 | ns    |
| t <sub>d(off)</sub>                     | Turn–Off Delay Time                            |                                                                                                                                                                              |     | 87                | 139                | ns    |
| t <sub>f</sub>                          | Turn–Off Fall Time                             |                                                                                                                                                                              |     | 40                | 64                 | ns    |
| Q <sub>g</sub>                          | Total Gate Charge                              | V <sub>DS</sub> = 15V,    I <sub>D</sub> = 16.8 A,<br>V <sub>GS</sub> = 5 V                                                                                                  |     | 45                | 63                 | nC    |
| Q <sub>gs</sub>                         | Gate–Source Charge                             |                                                                                                                                                                              |     | 13                |                    | nC    |
| Q <sub>gd</sub>                         | Gate–Drain Charge                              |                                                                                                                                                                              |     | 12                |                    | nC    |


# Electrical Characteristics (continued)

T<sub>A</sub> = 25°C unless otherwise noted

| Symbol                                                        | Parameter                                             | Test Conditions                                        | Min | Typ | Max | Units |
|---------------------------------------------------------------|-------------------------------------------------------|--------------------------------------------------------|-----|-----|-----|-------|
| <b>Drain–Source Diode Characteristics and Maximum Ratings</b> |                                                       |                                                        |     |     |     |       |
| I <sub>S</sub>                                                | Maximum Continuous Drain–Source Diode Forward Current |                                                        |     |     | 3.2 | A     |
| V <sub>SD</sub>                                               | Drain–Source Diode Forward Voltage                    | V <sub>GS</sub> = 0 V, I <sub>S</sub> = 3.2 A (Note 2) |     | 0.7 | 1.2 | V     |

## Notes:

1. R<sub>θJA</sub> is the sum of the junction-to-case and case-to-ambient thermal resistance where the case thermal reference is defined as the solder mounting surface of the drain pins. R<sub>θJC</sub> is guaranteed by design while R<sub>θCA</sub> is determined by the user's board design.



a) R<sub>θJA</sub> = 40°C/W when mounted on a 1in<sup>2</sup> pad of 2 oz copper



b) R<sub>θJA</sub> = 96°C/W when mounted on a minimum pad.

Scale 1 : 1 on letter size paper

2. Pulse Test: Pulse Width < 300μs, Duty Cycle < 2.0%

3. Maximum current is calculated as: 
$$\sqrt{\frac{P_D}{R_{DS(ON)}}}$$

where P<sub>D</sub> is maximum power dissipation at T<sub>C</sub> = 25°C and R<sub>DS(on)</sub> is at T<sub>J(max)</sub> and V<sub>GS</sub> = 10V. Package current limitation is 21A

# Typical Characteristics




Figure 1. On-Region Characteristics




Figure 2. On-Resistance Variation with Drain Current and Gate Voltage




Figure 3. On-Resistance Variation with Temperature




Figure 4. On-Resistance Variation with Gate-to-Source Voltage




Figure 5. Transfer Characteristics




Figure 6. Body Diode Forward Voltage Variation with Source Current and Temperature

# Typical Characteristics




Figure 7. Gate Charge Characteristics




Figure 8. Capacitance Characteristics




Figure 9. Maximum Safe Operating Area




Figure 10. Single Pulse Maximum Power Dissipation




Figure 11. Transient Thermal Response Curve

Thermal characterization performed using the conditions described in Note 1b.  
Transient thermal response will change depending on the circuit board design.

## TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

|                                   |                                  |                                  |                           |
|-----------------------------------|----------------------------------|----------------------------------|---------------------------|
| ACE <sup>Ex</sup> <sup>TM</sup>   | FAST <sup>®</sup>                | PACMAN <sup>TM</sup>             | SuperSOT <sup>TM</sup> -3 |
| Bottomless <sup>TM</sup>          | FAST <sup>r</sup> <sup>TM</sup>  | POP <sup>TM</sup>                | SuperSOT <sup>TM</sup> -6 |
| CoolFET <sup>TM</sup>             | GlobalOptoisolator <sup>TM</sup> | PowerTrench <sup>®</sup>         | SuperSOT <sup>TM</sup> -8 |
| CROSSVOLT <sup>TM</sup>           | GTO <sup>TM</sup>                | QFET <sup>TM</sup>               | SyncFET <sup>TM</sup>     |
| DenseTrench <sup>TM</sup>         | HiSeC <sup>TM</sup>              | QS <sup>TM</sup>                 | TinyLogic <sup>TM</sup>   |
| DOME <sup>TM</sup>                | ISOPLANAR <sup>TM</sup>          | QT Optoelectronics <sup>TM</sup> | UHC <sup>TM</sup>         |
| EcoSPARK <sup>TM</sup>            | LittleFET <sup>TM</sup>          | Quiet Series <sup>TM</sup>       | UltraFET <sup>®</sup>     |
| E <sup>2</sup> CMOS <sup>TM</sup> | MicroFET <sup>TM</sup>           | SILENT SWITCHER <sup>®</sup>     | VCX <sup>TM</sup>         |
| EnSigna <sup>TM</sup>             | MICROWIRE <sup>TM</sup>          | SMART START <sup>TM</sup>        |                           |
| FACT <sup>TM</sup>                | OPTOLOGIC <sup>TM</sup>          | Star* Power <sup>TM</sup>        |                           |
| FACT Quiet Series <sup>TM</sup>   | OPTOPLANAR <sup>TM</sup>         | Stealth <sup>TM</sup>            |                           |

## DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

## LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

## PRODUCT STATUS DEFINITIONS

### Definition of Terms

| Datasheet Identification | Product Status         | Definition                                                                                                                                                                                                            |
|--------------------------|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Advance Information      | Formative or In Design | This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.                                                                                    |
| Preliminary              | First Production       | This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design. |
| No Identification Needed | Full Production        | This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.                                                       |
| Obsolete                 | Not In Production      | This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.                                                   |



**ООО «НИОКРсистемс»** - это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

### **Наша компания это:**

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование
- Работаем по 275 ФЗ