THIS DRAWING IS UNPUBLISHED.
VERTRAULICHE UNVEROEFFENTLICHTE ZEICHNUNG


RELEASED FOR PUBLICATION
FREI FUER VEROEFFENTLICHUNG


© COPYRIGHT – By –
ALL RIGHTS RESERVED.
ALLE RECHTE VORBEHALTEN


LOC	DIST
—	—


REVISIONS
AENDERUNGEN


P	LTR	DESCRIPTION BESCHREIBUNG	DATE	DWN	APVD
	E1	PN 215298–2 AND 1–215298–5 REACTIVATED	30JUN2015	KJK	PS











P.C.–BOARD HOLE–PATTERN

POS.	L	PART NUMBER	
–	–	–	
2	5.08	215 298–2	
3	7.62	–3	OBSOLETE
4	10.16	–4	OBSOLETE
5	12.70	–5	
6	15.24	–6	
7	17.78	–7	
8	20.32	–8	
9	22.86	–9	OBSOLETE
10	25.40	1– –0	OBSOLETE
11	27.94	1– –1	
12	30.48	1– –2	OBSOLETE
13	33.02	1– –3	OBSOLETE
14	35.56	1– –4	
15	38.10	1– –5	
16	40.64	1– –6	
17	43.18	1– –7	OBSOLETE
18	45.72	1– –8	OBSOLETE
19	48.26	1– –9	
20	50.80	2– –0	
21	53.34	2– –1	OBSOLETE
22	55.88	2– –2	
23	58.42	2– –3	
24	60.96	2– –4	
25	63.50	2– –5	OBSOLETE
26	66.04	2– –6	OBSOLETE
27	68.58	2– –7	
28	71.12	2– –8	
29	73.66	2– –9	
30	76.20	3– –0	OBSOLETE
31	78.74	3– –1	
32	81.28	3– –2	
33	83.82	3– –3	
34	86.36	3– –4	
35	88.90	3– –5	
36	91.44	3– 215 298–6	

NOTES:

1. TO DETERMINE DIMENSIONS TAKE N = NO. OF POS.
FOR EXAMPLE: 10 POS.: N x 2,54 = 25,4 mm.
FOR ORDER NO. USE BASIC NO. + NO. OF POS.
FOR EXAMPLE: 2 POS.= 215 298–2 (SHORTEST VERSION)
36 POS.= 3–215 298–6 (LONGEST VERSION)
2. HOUSING MATERIAL: GREEN GLASSFILLED POLYESTER, UL 94V–0
CONTACT MATERIAL: PHOSPHOR BRONZE.
3. PLATING: 2.5–4.0µm TIN OVER MIN 0.5µm NICKEL
4. MATES WITH 0,63 SQUARE/ROUND MODU POSTS.
5. CONTACT–POINT.
6. RECOMMENDED P.C.BOARD–THICKNESS: 1,6mm.
7. RETENTION FEATURE.
8. RETENTION FORCE MUST BE MIN. 5N PER CONTACT
9. HV100 CONNECTOR PACKED IN ANTISTATIC BLISTER TRAY

VERWENDET FÜR
E 92–9803

THIS DRAWING IS A CONTROLLED DOCUMENT.
DIESE ZEICHNUNG IST EIN KONTROLLIERTES DOKUMENT.

DIMENSIONS: MASSEANHEITEN: mm

TOLERANCES UNLESS OTHERWISE SPECIFIED: ALLGEMEINTOLERANZEN: ±0.1mm
0 PLC ± –
1 PLC ± –
2 PLC ± –
3 PLC ± –
4 PLC ± –
ANGLES/WINKEL ± –

MATERIAL: SEE NOTES

FINISH/OBERFLAECHE/FARBE: SEE NOTES

DWN	A.HO	24.02.89
CHK	M.SCHAARSCHMIDT	24.02.89
APVD	G.FELDMEIER	–
PRODUCT SPEC PRODUKTSPEZ.	108–19056	
APPLICATION SPEC VERARBEITUNGSSPEZ.	—	
WEIGHT GEWICHT	—	

TE Connectivity

NAME
HV 100 VERTICAL CONNECTOR
SINGLE ROW, 7,0mm HEIGHT,
TOP ENTRY, TIN, MAX, 36 POSITIONS.

SIZE	CAGE CODE	DRAWING NO ZEICHNUNGS–NR.	RESTRICTED TO NUR FUER
A3	00779	C–215298	—

CUSTOMER DRAWING/KUNDENZEICHNUNG | SCALE MASSSTAB 5:1 | SHEET BLATT 1 OF 1 | REV E1

ООО «НИОКРсистемс» - это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

Наша компания это:

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование
- Работаем по 275 ФЗ

ООО «НИОКР СИТЕМС»
Москва, 125362, Россия, ул. Вишневая, д. 9, к. 1, Блок 104 а и 104 в

Телефон: 8 (495) 268-14-82
Email: n@nsistems.ru

ИНН: 7735154786
ОГРН: 1167746717709