




General ordering data	
Order No.	1031300000
Part designation	WDL 2.5/S/L
Version	Storey installation terminal, 2.5 mm², Screw connection, Wemid, dark beige, TS 35
EAN	4008190110598
Qty.	50 pc(s).

Product notes	
Note, ordering data	WDL 2.5/S/N order no. 1031300000 (connection marked blue)
Product description	Space-saving wiring of three-phase circuits using only two terminals.

2 clampable conductors (H05V/H07V) with equal cross-section (rated connection)	
Solid, min.	0.5 mm²
Solid, max.	1.5 mm²
Flexible, min.	0.5 mm²
Flexible, max.	1.5 mm²
Flexible with ferrule, min. (DIN 46228 pt 1)	0.5 mm²
Flexible with ferrule, max. (DIN 46228 pt 1)	1.5 mm²

Additional technical data	
Colour of insulating material	dark beige
Connection direction	on side
End plate required	Yes
Explosion-tested version "Ex e"	No
Installation advice	TS 35
Insulating material	Wemid
Levels cross-connected internally	No
No. of identical terminals	1
No. of levels	2
No. of terminal strips per level	2
Open sides	right

Additional technical data	
Operating temperature range	- 50 °C, + 120 °C
Product family	W-Series
Type of connection	Screwed
Type of mounting	Snap-on
UL 94 flammability rating of insulation material	V-0
Version	Distribution terminal for N rail

CSA rating data	
Voltage (CSA)	300 V
CSA current	10 A
Min. cross-section (CSA)	AWG 26
Max. cross-section (CSA)	AWG 12

Conductors for clamping (additional connection)	
Flexible with ferrule, min. (DIN 46228 pt 1)	0.5 mm²
Flexible with ferrule, max. (DIN 46228 pt 1)	2.5 mm²

Conductors for clamping (rated connection)	
Clamping range, min.	0.13 mm²
Clamping range, max.	4 mm²
Type of connection	Screw connection
2nd type of connection	screwed
Connection direction	on side
No. of connections	2
Stripping length	8 mm
Clamping screw	M 2.5
Blade size	0.6 x 3.5 mm
Tightening torque range	0.4...0.6 Nm
Torque level with DMS electric screwdriver	1
Gauge to IEC 60947-1	A3
Solid, min.	0.5 mm²
Solid, max.	4 mm²
Stranded, min.	1.5 mm²
Stranded, max.	4 mm²
Flexible, min.	0.5 mm²
Flexible, max.	4 mm²
Flexible with ferrule, min. (DIN 46228/1)	0.5 mm²
Flexible with ferrule, max. (DIN 46228/1)	2.5 mm²
Flexible, min., ferrule with plastic collar (DIN 46228 pt 4)	0.5 mm²
Flexible, max., ferrule with plastic collar (DIN 46228 pt 4)	4 mm²
AWG conductor size, min.	AWG 26
AWG conductor size, max.	AWG 12
AWG conductor size, min.	0.13 mm²
AWG conductor size, max.	3.31 mm²

Dimensions	
Width	6.1 mm
Height of lowest version	49 mm

Dimensions	
Length	84.5 mm
TS 35 offset	48.1 mm
Disconnect terminals	
Torque level with DMS electric screwdriver	1
N-conductor disconnect terminal	
For N-busbar	3 x 10 mm
Rating data	
Rated cross-section	2.5 mm²
Rated voltage	400 V
Rated impulse voltage	6 kV
Rated current	24 A
Standards	IEC 60947-7-1
Current with max. conductor	32 A
Pollution severity	3
UL rating data	
Voltage (UL)	300 V
Current (UL)	15 A
Min. cross-section (UL)	AWG 22
Max. cross-section (UL)	AWG 12
Approvals	
Approvals institutes	
Classifications	
eClass 4.1	27-14-11-25
eClass 5.0	27-14-11-25
eClass 5.1	27-14-11-25

Similar products

Order No.	Part designation	Version
1030400000	WDL 2.5/L	Storey installation terminal, 2.5 mm², Screw connection, Wemid, dark beige, TS 35
1030300000	WDL 2.5/L/L	Storey installation terminal, 2.5 mm², Screw connection, Wemid, dark beige, TS 35
1030200000	WDL 2.5/L/L/PE	Storey installation terminal, 2.5 mm², Screw connection, Wemid, dark beige, TS 35
1030000000	WDL 2.5/N/L	Storey installation terminal, 2.5 mm², Screw connection, Wemid, dark beige, TS 35
1029900000	WDL 2.5/N/L/PE	Storey installation terminal, 2.5 mm², Screw connection, Wemid, dark beige, TS 35

	1031200000	WDL 2.5/S/L/L	Storey installation terminal, 2.5 mm², Screw connection, Wemid, dark beige, TS 35
	1031100000	WDL 2.5/S/L/L/PE	Storey installation terminal, 2.5 mm², Screw connection, Wemid, dark beige, TS 35
	1030900000	WDL 2.5/S/N	Storey installation terminal, 2.5 mm², Screw connection, Wemid, dark beige, TS 35
	1030800000	WDL 2.5/S/N/L	Storey installation terminal, 2.5 mm², Screw connection, Wemid, dark beige, TS 35
	1030700000	WDL 2.5/S/N/L/PE	Storey installation terminal, 2.5 mm², Screw connection, Wemid, dark beige, TS 35

ООО «НИОКРсистемс» - это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

Наша компания это:

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование
- Работаем по 275 ФЗ

ООО «НИОКР СИТЕМС»
Москва, 125362, Россия, ул. Вишневая, д. 9, к. 1, Блок 104 а и 104 в

Телефон: 8 (495) 268-14-82
Email: n@nsistems.ru

ИНН: 7735154786
ОГРН: 1167746717709