
Screw Type Series

311 Series



Technical Data:

Material

- HOUSING: NYLON UL 94 V-0.
- Metal Housing: Brass (Cu Zn) Cu, Tin plated.
- Wire guard: Stainless steel.
- Screw: Steel galvanized and chromatized, M2.6

Electrical:


- Current rating: 10 Amps/way max.
- Contact resistance: 20m Ω (Max).
- Insulation resistance: 5000M Ω /1000V.
- Withstanding Voltage: 1500VAC (1min). test time= 60sec/1pcs.
- Operation Voltage: 300 VAC.
- Wire Range: 14-22 AWG.

Mechanical:

- Torque: 4 Kg. cm (Max).
- Operating temperature: –55°C to +105°C
- Solderability: 95 % coverage (min). test temperature= 230°C±10°C. test time= 3sec ± 0.5sec.

Application and Features:

- Standard sizes are 2 and 3 way-block, but every number of contact can be combined, by simply plugging them together and can be ordered as required.
- With wire guard for wire protection (for that the screw doesn't press directly on the wire)



Notes: Please replace 'X' with appropriate coding listed in the tables below

3	1	1	–	X	X	X	–	X	X	0	2	–	0	0	X	0

Number of contact		Pitch		Wire Guard		Color		Screw Type	
02-24 po	02	5.00mm/.197"	1	Without	0	Black	0	"_"	0
	03	10.00mm/.394"	2	With	1	Green	5	"+"	1
	etc.	5.08mm/.200"	A			Blue	6		
		10.16mm/.400"	B						

DB LECTRO Inc. 3600 boul. Matte suite i Brossard Qc J4Y-2Z2 tel:(450)-444-1424 fax:(450)-444-4714

ООО «НИОКРсистемс» - это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

Наша компания это:

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование
- Работаем по 275 ФЗ

ООО «НИОКР СИТЕМС»
Москва, 125362, Россия, ул. Вишневая, д. 9, к. 1, Блок 104 а и 104 в

Телефон: 8 (495) 268-14-82
Email: n@nsistems.ru

ИНН: 7735154786
ОГРН: 1167746717709