CP SNT 24W 5V 2A

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-2083
www.weidmueller.com



One-phase switched-mode power unit in installation housing in performance classes 24 and 48 W. .
The INSTA power units can be universally deployed because of their wide input range from 85 V AC to 265 V AC.
They are available with output voltages from 5 V to 48 V.

General ordering data

Order No.	9928890005
Part designation	CP SNT 24W 5V 2A
Version	Power supply, switch-mode power supply unit, 5 V
GTIN (EAN)	4032248217526
Qty.	1 pc(s).

CP SNT 24W 5V 2A

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-2083
www.weidmueller.com

Technical data

Dimensions (1)

Length	62.5 mm	Width	52 mm
Height	90.5 mm		

temperature

Ambient temperature (operational)		Storage temperature	-40 °C...+85 °C

Input

Conductor connection system	Screw connection	DC input voltage range	120…300 V DC
Input current	460 mA @ 115 V AC; 250 mA @ 230 V AC	Input current at 115 Vac	460 mA RMS ± 20%
Input current at 125 Vdc	235 mA ± 20%	Input current at 250 Vdc	120 mA ± 20%
Input frequency	50/ 60 Hz	Input fuse	2 A time-lag fuse (internal)
Input voltage (voltage mode input)	85...265 V AC, 120...300 V DC	Input voltage range AC	85…265 V AC
Surge protection	Varistor	making current limit	Thermistor

output

Conductor connection system	Screw connection	Control at 10...100% load	0.5 %
Control at input voltage	0.2 %	Mains failure bridge-over time	35 ms @ 115 V AC / 160 ms @ 230 V AC
Mains failure bridge-over time for 115 V AC	35 ms	Mains failure bridge-over time for 230 V AC	160 ms
Max. capacitance at output	8000 µF	Max. residual ripple	< 2 %
Output current	2 A	Output power, max.	10 W
Output voltage	5 V	Output voltage type	DC
Overload protection	**Surge current** / thermal cut-out	Surge protection	Varistor

General data

Ambient temperature (operational)		DIN Rail compatibility	TS 35
Degree of efficiency at max. load	78 %	EMC standards	EN 61000-6 /-2, -3
Mounting position, installation notice	horizontally on terminal rail TS 35	Standards	EN 50178 EN 60950 IEC950
Ambient temperature (operational)	-20 °C...+50 °C		

Insulation coordination

electrical isolation, I/O rail	4 kV	electrical isolation, input-earth	1.5 kV
electrical isolation, input-output	3 kV	electrical isolation, output-earth	0.5 kV

Connection data

Clamping range, nom.	4 mm²	Clamping range, min.	0.08 mm²
Clamping range, max.	4 mm²		

Approvals

Approvals institutes	CSA; GOSTME25; CE

Classifications

eClass 6.0	27-04-90-04

CP SNT 24W 5V 2A

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-2083
www.weidmueller.com

Technical data

Notes


Note, technical data	Derating loss: 33% @ 60°C The internal varistor found in a switch-mode power supply does not replace the need for surge protection within a system.

CP SNT 24W 5V 2A

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-2083
www.weidmueller.com

Drawings

Electric symbol



ООО «НИОКРсистемс» - это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

Наша компания это:

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование
- Работаем по 275 ФЗ

ООО «НИОКР СИТЕМС»
Москва, 125362, Россия, ул. Вишневая, д. 9, к. 1, Блок 104 а и 104 в

Телефон: 8 (495) 268-14-82
Email: n@nsistems.ru

ИНН: 7735154786
ОГРН: 1167746717709