

TAA-Compliant Internet Office 120V 600VA 300W Standby UPS, Ultra-Compact Desktop, USB

MODEL NUMBER: INTERNET600TAA







Description

Features

Ultra-compact standby UPS with built-in USB monitoring port protects PCs, network workstations and other systems reliant upon a USB interface for UPS monitoring and unattended system shutdown. Maintains AC output during blackouts and brownouts starting at 99V. Includes USB monitoring with cabling, TEL/DSL line surge suppression, surge-only outlets and LED indicators. PowerAlert software available free via download.

- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases
- This product is ENERGY STAR qualified for its ability to save customers money while helping to protect the environment
- INTERNET600TAA standby UPS offers protection from blackouts, brownouts and surges on both AC and dialup modem lines
- · Provides seamless battery derived AC output during blackouts and severe brownouts so that connected equipment can be shut down without data loss
- USB port enables data-saving unattended shutdown when used with Tripp Lite's PowerAlert software, available via FREE download from www.tripplite.com/poweralert
- HID-compliant USB also enables integration with built-in power management and auto shutdown features of Windows and Mac OS X
- 4 battery supported outlets protect computer, monitor and other vital system peripherals, plus 4 additional surge suppression-only outlets for printers and other system accessories not requiring battery support
- · Attractive stealth black UPS color scheme
- Single line phone jacks with line splitter protects peripherals with a standard dialup phone line connection
- · Audible alarm and front panel LEDs offer continuous status information regarding line and battery power operation
- . 600VA /300 watt power handling ability supports entry-level PC systems for several minutes during power fail conditions
- Includes attached 6 ft. AC power cord, on/off power switch
- Compatible with 120V/60 Hz applications in USA, Canada, Mexico and other countries
- Optional PDUB15 bypass PDU enables hot-swappable UPS replacement with no disruption to connected equipment

Specifications

Highlights

- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases
- 600VA ultra-compact 120V standby UPS
- 4 UPS battery supported outlets,
 4 surge-only outlets
- USB, TEL/DSL protection, Wall mountable, 99% efficient
- NEMA 5-15P input plug and 8
 NEMA 5-15R outlets
- This product is ENERGY STAR qualified for its ability to save customers money while helping to protect the environment

Package Includes

- INTERNET600TAA UPS system
- USB cable
- Instruction manual



ОИТРИТ		
Output Volt Amp Capacity (VA)	600	
Output Watt Capacity (Watts)	300	
Nominal Output Voltage(s) Supported	110V; 115V; 120V	
Nominal Voltage Details	115v nominal output in battery mode	
Frequency Compatibility	60 Hz	
Output Voltage Regulation (Battery Mode)	+/- 5%	
Output Receptacles	(8) 5-15R	
UPS Output Receptacles (Surge Suppression Only)	4 UPS outlets, 4 surge-only outlets	
Hot-Swap PDU options	PDUB15 (2U / 8 5-15R outlets)	
Output AC Waveform (AC Mode)	Sine wave	
Output AC Waveform (Battery Mode)	PWM sine wave	
INPUT		
Rated input current (Maximum Load)	10A	
Nominal Input Voltage(s) Supported	120V AC	
UPS Input Connection Type	5-15P; Right-Angled	
Input Circuit Breakers	10A	
UPS Input Cord Length (ft.)	6	
UPS Input Cord Length (m)	1.8	
Recommended Electrical Service	15A 120V	
Input Phase	Single-Phase	
BATTERY		
Half Load Runtime (min.)	9.9 min. (150w)	
DC System Voltage (VDC)	12	
Expandable Runtime	No	
USER INTERFACE, ALERTS & CONTROLS		
Switches	Combination switch controls on/off power status and self-test operation	
Audible Alarm	Audible alarm indicates power-failure and overload status	
LED Indicators	2 LEDs indicate power status and overload/check battery status	
SURGE / NOISE SUPPRESSION		



UPS AC Suppression Joule Rating UPS AC Suppression Response Time Instantaneous UPS Dataline Suppression 1 line TEL/DSL (1 in / 1 out) EMI / RFI AC Noise Suppression Yes PHYSICAL Included Mounting Accessory Description Unstallation Form Factors Supported with Included Accessories Primary Form Factor UPS Power Module Dimensions (hwd, in.) UPS Power Module Dimensions (hwd, cm) 7.8 x 27.6 x 14.6	
Time	
PHYSICAL Included Mounting Accessory Description Installation Form Factors Supported with Included Accessories Primary Form Factor UPS Power Module Dimensions (hwd, in.) Yes Wallmount installation supported using keyhole mounting tabs Tower; Ultra-compact desktop 3.1 x 10.8 x 5.7 UPS Power Module Dimensions 7.8 x 27.6 x 14.6	
PHYSICAL Included Mounting Accessory Description Wallmount installation supported using keyhole mounting tabs Installation Form Factors Supported with Included Accessories Primary Form Factor Desktop UPS Power Module Dimensions (hwd, in.) UPS Power Module Dimensions 7.8 x 27.6 x 14.6	
Included Mounting Accessory Description Wallmount installation supported using keyhole mounting tabs Installation Form Factors Supported with Included Accessories Primary Form Factor Desktop UPS Power Module Dimensions (hwd, in.) 7 8 x 27 6 x 14 6	
Description Installation Form Factors Supported with Included Accessories Primary Form Factor Desktop UPS Power Module Dimensions (hwd, in.) UPS Power Module Dimensions 7 8 x 27 6 x 14 6	
with Included Accessories Primary Form Factor Desktop UPS Power Module Dimensions (hwd, in.) UPS Power Module Dimensions 7.8 x 27.6 x 14.6	
UPS Power Module Dimensions (hwd, in.) 3.1 x 10.8 x 5.7 UPS Power Module Dimensions 7.8 x 27.6 x 14.6	
(hwd, in.) UPS Power Module Dimensions 7.8 x 27.6 x 14.6	
(invo, on)	
UPS Power Module Weight (lbs.) 6.5	
UPS Power Module Weight (kg) 2.95	
UPS Shipping Dimensions (hwd / in.) 4.1 x 8 x 13	
UPS Shipping Dimensions (hwd / cm) 10.4 x 20.3 x 33	
Shipping Weight (lbs.) 7	
Shipping Weight (kg) 3.2	
UPS Housing Material ABS	
Primary UPS Height (mm) 79	
Primary UPS Width (mm) 274	
Primary UPS Depth (mm) 145	
Shipping Height (mm) 104	
Shipping Width (mm) 203	
Shipping Depth (mm) 330	
ENVIRONMENTAL	
Operating Temperature Range +32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius.	
Storage Temperature Range +5 to +122 degrees Fahrenheit / -15 to +50 degrees Celsius.	
Relative Humidity 0 to 95%, non-condensing	
AC Mode BTU / Hr. (Full Load) 14	
Battery Mode BTU / Hr. (Full Load) 210	
AC Mode Efficiency Rating (100% Load) 99%	



COMMUNICATIONS	
Communications Interface	USB (HID enabled)
Communications interface	
PowerAlert Software	For local monitoring via the UPS's built-in USB port, download PowerAlert Local software at http://www.tripplite.com/poweralert
Communications Cable	RJ to USB interface cable included
WatchDog Compatibility	Supports Watchdog application, OS and hard-reboot restart options for remote applications
Network UPS Tools Compatibility	NUT compatible. See the full list of Tripp Lite NUT compatible UPS systems at http://www.networkupstools.org/stable-hcl.html?manufacturer=Tripp Lite
LINE / BATTERY TRANSFER	
Transfer Time	2-4 milliseconds
Low Voltage Transfer to Battery Power (Setpoint)	99
High Voltage Transfer to Battery Power (Setpoint)	139
SPECIAL FEATURES	
Cold Start (Startup in Battery Mode During a Power Failure)	Cold-start operation supported
Green Energy-Saving Features	Greater than 95% efficiency - GREEN UPS
CERTIFICATIONS	
UPS Certifications	Tested to UL1778 (USA); Tested to CSA (Canada); Tested to NOM (Mexico); Meets FCC Part 15 Category B (EMI); TAA Compliant; ENERGY STAR Qualified
WARRANTY	
Product Warranty Period (U.S. & Canada)	3-year limited warranty
Product Warranty Period (Latin America)	3-year limited warranty
Product Warranty Period (International)	2-year limited warranty
Product Warranty Period (Mexico)	3-year limited warranty
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$100,000 Ultimate Lifetime Insurance

© 2017 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

https://www.tripplite.com/products/product-certification-agencies



ооо «ниокрсистемс» - это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

Наша компания это:

• Гарантия качества поставляемой продукции

Телефон: 8 (495) 268-14-82

Email: n@nsistems.ru

ИНН: 7735154786 ОГРН: 1167746717709

- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование
- Работаем по 275 Ф3