ALPHA & OMEGA SEMICONDUCTOR


AO4612
Complementary Enhancement Mode Field Effect Transistor

General Description


The AO4612 uses advanced trench technology MOSFETs to provide excellent $R_{DS(ON)}$ and low gate charge. The complementary MOSFETs may be used in H-bridge, Inverters and other applications. *Standard product AO4612 is Pb-free (meets ROHS & Sony 259 specifications). AO4612L is a Green Product ordering option. AO4612 and AO4612L are electrically identical.*

Features


n-channel	p-channel
V_{DS} (V) = 60V	-60V
I_D = 4.5A (V_{GS}=10V)	-3.2A (V_{GS} = -10V)
$R_{DS(ON)}$	$R_{DS(ON)}$
< 56mΩ (V_{GS}=10V)	< 105mΩ (V_{GS} = -10V)
< 77mΩ (V_{GS}=4.5V)	< 135mΩ (V_{GS} = -4.5V)



SOIC-8



n-channel



p-channel

Absolute Maximum Ratings T_A=25°C unless otherwise noted

Parameter		Symbol	Max n-channel	Max p-channel	Units
Drain-Source Voltage		V_{DS}	60	-60	V
Gate-Source Voltage		V_{GS}	±20	±20	V
Continuous Drain Current [A]	T_A=25°C	I_D	4.5	-3.2	A
	T_A=70°C		3.6	-2.6	
Pulsed Drain Current [B]		I_{DM}	20	-20	
Power Dissipation	T_A=25°C	P_D	2	2	W
	T_A=70°C		1.28	1.28	
Junction and Storage Temperature Range		T_J, T_{STG}	-55 to 150	-55 to 150	°C

Thermal Characteristics: n-channel and p-channel

Parameter		Symbol	Device	Typ	Max	Units
Maximum Junction-to-Ambient [A]	t ≤ 10s	$R_{\theta JA}$	n-ch	48	62.5	°C/W
Maximum Junction-to-Ambient [A]	Steady-State		n-ch	74	110	°C/W
Maximum Junction-to-Lead [C]	Steady-State	$R_{\theta JL}$	n-ch	35	60	°C/W
Maximum Junction-to-Ambient [A]	t ≤ 10s	$R_{\theta JA}$	p-ch	48	62.5	°C/W
Maximum Junction-to-Ambient [A]	Steady-State		p-ch	74	110	°C/W
Maximum Junction-to-Lead [C]	Steady-State	$R_{\theta JL}$	p-ch	35	40	°C/W

N Channel Electrical Characteristics (T_J=25°C unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
STATIC PARAMETERS						
BV_{DSS}	Drain-Source Breakdown Voltage	I_D=250μA, V_{GS}=0V	60			V
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS}=48V, V_{GS}=0V			1	μA
		T_J=55°C			5	
I_{GSS}	Gate-Body leakage current	V_{DS}=0V, V_{GS}= ±20V			100	nA
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}=V_{GS} I_D=250μA	1	2.1	3	V
$I_{D(ON)}$	On state drain current	V_{GS}=10V, V_{DS}=5V	20			A
$R_{DS(ON)}$	Static Drain-Source On-Resistance	V_{GS}=10V, I_D=4.5A		46	56	mΩ
		T_J=125°C		79		
		V_{GS}=4.5V, I_D=3A		64	77	mΩ
g_{FS}	Forward Transconductance	V_{DS}=5V, I_D=4.5A		11		S
V_{SD}	Diode Forward Voltage	I_S=1A,V_{GS}=0V		0.74	1	V
I_S	Maximum Body-Diode Continuous Current				3	A
DYNAMIC PARAMETERS						
C_{iss}	Input Capacitance	V_{GS}=0V, V_{DS}=30V, f=1MHz		450	540	pF
C_{oss}	Output Capacitance			60		pF
C_{rss}	Reverse Transfer Capacitance			25		pF
R_g	Gate resistance	V_{GS}=0V, V_{DS}=0V, f=1MHz		1.65	2	Ω
SWITCHING PARAMETERS						
Q_g(10V)	Total Gate Charge	V_{GS}=10V, V_{DS}=30V, I_D=4.5A		8.5	10.5	nC
Q_g(4.5V)	Total Gate Charge			4.3	5.5	nC
Q_{gs}	Gate Source Charge			1.6		nC
Q_{gd}	Gate Drain Charge			2.2		nC
$t_{D(on)}$	Turn-On DelayTime	V_{GS}=10V, V_{DS}=30V, R_L=6.7Ω, R_{GEN}=3Ω		4.7	7	ns
t_r	Turn-On Rise Time			2.3	4.5	ns
$t_{D(off)}$	Turn-Off DelayTime			15.7	24	ns
t_f	Turn-Off Fall Time			1.9	4	ns
t_{rr}	Body Diode Reverse Recovery Time	I_F=4.5A, dI/dt=100A/μs		27.5	35	ns
Q_{rr}	Body Diode Reverse Recovery Charge	I_F=4.5A, dI/dt=100A/μs		32		nC

A: The value of $R_{\theta JA}$ is measured with the device mounted on 1in^2 FR-4 board with 2oz. Copper, in a still air environment with T_A=25°C. The value in any given application depends on the user's specific board design. The current rating is based on the t≤ 10s thermal resistance rating.

B: Repetitive rating, pulse width limited by junction temperature.

C. The $R_{\theta JA}$ is the sum of the thermal impedence from junction to lead $R_{\theta JL}$ and lead to ambient.

D. The static characteristics in Figures 1 to 6 are obtained using 80μs pulses, duty cycle 0.5% max.

E. These tests are performed with the device mounted on 1 in^2 FR-4 board with 2oz. Copper, in a still air environment with T_A=25°C. The SOA curve provides a single pulse rating.

Rev2: August 2005

THIS PRODUCT HAS BEEN DESIGNED AND QUALIFIED FOR THE CONSUMER MARKET. APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS: N-CHANNEL




Fig 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: On-Resistance vs. Gate-Source Voltage




Figure 6: Body-Diode Characteristics

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS: N-CHANNEL




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area (Note E)




Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note E)




Figure 11: Normalized Maximum Transient Thermal Impedance

P-Channel Electrical Characteristics (T_J=25°C unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
STATIC PARAMETERS						
BV_{DSS}	Drain-Source Breakdown Voltage	I_D=-250µA, V_{GS}=0V	-60			V
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS}=-48V, V_{GS}=0V			-1	µA
		T_J=55°C			-5	
I_{GSS}	Gate-Body leakage current	V_{DS}=0V, V_{GS}=±20V			±100	nA
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}=V_{GS} I_D=-250µA	-1	-2.1	-3	V
$I_{D(ON)}$	On state drain current	V_{GS}=-10V, V_{DS}=-5V	-20			A
$R_{DS(ON)}$	Static Drain-Source On-Resistance	V_{GS}=-10V, I_D=-3.2A		84	105	mΩ
		T_J=125°C		145		
		V_{GS}=-4.5V, I_D=-2.8A		106	135	mΩ
g_{FS}	Forward Transconductance	V_{DS}=-5V, I_D=-3.2A		9		S
V_{SD}	Diode Forward Voltage	I_S=-1A,V_{GS}=0V		-0.73	-1	V
I_S	Maximum Body-Diode Continuous Current				-3	A
DYNAMIC PARAMETERS						
C_{iss}	Input Capacitance	V_{GS}=0V, V_{DS}=-30V, f=1MHz		930	1120	pF
C_{oss}	Output Capacitance			85		pF
C_{rss}	Reverse Transfer Capacitance			35		pF
R_g	Gate resistance	V_{GS}=0V, V_{DS}=0V, f=1MHz		7.2	9	Ω
SWITCHING PARAMETERS						
Q_g(10V)	Total Gate Charge (10V)	V_{GS}=-10V, V_{DS}=-30V, I_D=-3.2A		16	20	nC
Q_g(4.5V)	Total Gate Charge (4.5V)			8	10	nC
Q_{gs}	Gate Source Charge			2.5		nC
Q_{gd}	Gate Drain Charge			3.2		nC
$t_{D(on)}$	Turn-On DelayTime	V_{GS}=-10V, V_{DS}=-30V, R_L=9.4Ω, R_{GEN}=3Ω		8	12	ns
t_r	Turn-On Rise Time			3.8	7.5	ns
$t_{D(off)}$	Turn-Off DelayTime			31.5	48	ns
t_f	Turn-Off Fall Time			7.5	15	ns
t_{rr}	Body Diode Reverse Recovery Time	I_F=-3.2A, dI/dt=100A/µs		27	35	ns
Q_{rr}	Body Diode Reverse Recovery Charge	I_F=-3.2A, dI/dt=100A/µs		32		nC

A: The value of $R_{\theta JA}$ is measured with the device mounted on 1in^2 FR-4 board with 2oz. Copper, in a still air environment with T_A =25°C. The value in any given application depends on the user's specific board design. The current rating is based on the t≤ 10s thermal resistance rating.

B: Repetitive rating, pulse width limited by junction temperature.

C. The $R_{\theta JA}$ is the sum of the thermal impedence from junction to lead $R_{\theta JL}$ and lead to ambient.

D. The static characteristics in Figures 1 to 6,12,14 are obtained using 80µs pulses, duty cycle 0.5% max.

E. These tests are performed with the device mounted on 1 in^2 FR-4 board with 2oz. Copper, in a still air environment with T_A=25°C. The SOA curve provides a single pulse rating.

THIS PRODUCT HAS BEEN DESIGNED AND QUALIFIED FOR THE CONSUMER MARKET. APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE Rev2: August 2005

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS: P-CHANNEL




Fig 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: On-Resistance vs. Gate-Source Voltage




Figure 6: Body-Diode Characteristics

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS: P-CHANNEL




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area (Note E)




Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note E)




Figure 11: Normalized Maximum Transient Thermal Impedance

ООО «НИОКРсистемс» - это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

Наша компания это:

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование
- Работаем по 275 ФЗ

ООО «НИОКР СИТЕМС»
Москва, 125362, Россия, ул. Вишневая, д. 9, к. 1, Блок 104 а и 104 в

Телефон: 8 (495) 268-14-82
Email: n@nsistems.ru

ИНН: 7735154786
ОГРН: 1167746717709