How to select your CanStack motor

Selection Criteria

- The Torque – Speed Curves are essential for selecting the right motor and control drive method for a specific application.
- Define your application load – speed required, load inertia, torque and accuracy needed.
- If the application requires no acceleration, then use the pull out torque.
- If the load is inertial (acceleration is required), it is advisable to use pull in torque.
- Motor temperature rise is important – so ambient temperature and duty cycle are important selection factors
- It is advisable to use 1.5 to 2 times the margin over the maximum torque required.
- Choosing the correct drive is important – for example micro-stepping drives will provide quieter operation.
- Our engineering team is capable of designing a special coil with resistance and inductances to suit your needs.
- Remember – if it is not in the catalog – it does not mean that we cannot provide a solution for you - Portescap may still be able to design a product for your needs as our team can draw from a wealth of customized designs created over the past 40 years.

26M048D2B

CanStack Motor Designation

26	M	048	D	2	B
Motor Diameter (mm) 15 20 26 35 42 55	Rotor Dia S = Small M = Medium L = Large	Steps per Rev 020: 20 ppr 024: 24 ppr 048: 48 ppr 100: 100 ppr	Magnet Type B = Ferrite C = He Ferrite D = Neodymium	Voltage 1 = 5 V 2 = 12 V	Coil U = Unipolar B = Bipolar

НИОКР СИСТЕМС

ООО «НИОКРсистемс» - это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

Наша компания это:

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование
- Работаем по 275 ФЗ

ООО «НИОКР СИТЕМС»
Москва, 125362, Россия, ул. Вишневая, д. 9, к. 1, Блок 104 а и 104 в

Телефон: 8 (495) 268-14-82
Email: n@nsistems.ru

ИНН: 7735154786
ОГРН: 1167746717709