




# BAR46

## BAR46AFILM

### SMALL SIGNAL SCHOTTKY DIODES

#### FEATURES AND BENEFITS

- VERY SMALL CONDUCTION LOSSES
- NEGLIGIBLE SWITCHING LOSSES
- LOW FORWARD VOLTAGE DROP
- SURFACE MOUNT DEVICE



#### DESCRIPTION

High voltage Schottky rectifier suited for SLIC protection during the card insertion operation.

#### ABSOLUTE RATINGS(limiting values)

Symbol	Parameter	Value	Unit
V <sub>RRM</sub>	Repetitive peak reverse voltage	100	V
I <sub>F</sub>	Continuous forward current	150	mA
P <sub>tot</sub>	Power dissipation (note 1)	230	mW
T <sub>stg</sub>	Maximum storage temperature range	- 65 to +150	°C
T <sub>j</sub>	Maximum operating junction temperature *	150	°C
T <sub>L</sub>	Maximum temperature for soldering during 10s	260	°C

Note 1: for double diodes, P<sub>tot</sub> is the total dissipation of both diodes.

$$* : \frac{dP_{tot}}{dT_j} < \frac{1}{R_{th}(j-a)} \text{ thermal runaway condition for a diode on its own heatsink}$$

#### THERMAL RESISTANCE

Symbol	Parameter	Value	Unit
R <sub>th(j-a)</sub>	Junction-ambient *	500	°C/W

\* Mounted on epoxy board, with recommended pad layout.

## **BAR46 /BAR46AFILM**

### **ELECTRICAL CHARACTERISTICS**

#### **STATIC CHARACTERISTICS**

<b>Symbol</b>	<b>Test conditions</b>		<b>Min.</b>	<b>Typ.</b>	<b>Max.</b>	<b>Unit</b>
$V_{BR}$	$T_j = 25^\circ C$	$I_R = 100 \mu A$	100			V
$V_F$ *	$T_j = 25^\circ C$	$I_F = 0.1 mA$			0.25	V
	$T_j = 25^\circ C$	$I_F = 10 mA$			0.45	
	$T_j = 25^\circ C$	$I_F = 250 mA$			1	
$I_R$ **	$T_j = 25^\circ C$	$V_R = 1.5 V$			0.5	$\mu A$
	$T_j = 60^\circ C$				5	
	$T_j = 25^\circ C$	$V_R = 10 V$			0.8	
	$T_j = 60^\circ C$				7.5	
	$T_j = 25^\circ C$	$V_R = 50 V$			2	
	$T_j = 60^\circ C$				15	
	$T_j = 25^\circ C$	$V_R = 75 V$			5	
	$T_j = 60^\circ C$				20	


Pulse test : \*  $t_p = 380\mu s$   $\delta < 2\%$

\*\*  $t_p = 5 ms$ ,  $\delta < 2\%$


#### **DYNAMIC CHARACTERISTICS**

<b>Symbol</b>	<b>Test conditions</b>			<b>Min.</b>	<b>Typ.</b>	<b>Max.</b>	<b>Unit</b>
C	$T_j = 25^\circ C$	$V_R = 0 V$	$F = 1MHz$		10		$pF$
	$T_j = 25^\circ C$	$V_R = 1 V$			6		


**Fig. 1:** Forward current versus forward voltage at different temperatures (typical values).




**Fig. 2:** Forward current versus forward voltage (typical values).



**Fig. 3:** Reverse current versus junction temperature (typical values).




**Fig. 4:** Reverse current versus continuous reverse voltage (typical values).



## **BAR46 /BAR46AFILM**


---

**Fig. 5:** Capacitance C versus reverse applied voltage  $V_R$  (typical values).




## PACKAGE MECHANICAL DATA

SOT-23 (Plastic)



REF.	DIMENSIONS			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	0.89	1.4	0.035	0.055
A1	0	0.1	0	0.004
B	0.3	0.51	0.012	0.02
c	0.085	0.18	0.003	0.007
D	2.75	3.04	0.108	0.12
e	0.85	1.05	0.033	0.041
e1	1.7	2.1	0.067	0.083
E	1.2	1.6	0.047	0.063
H	2.1	2.75	0.083	0.108
L	0.6 typ.		0.024 typ.	
S	0.35	0.65	0.014	0.026

## FOOT PRINT DIMENSIONS (Millimeter)



Ordering type	Marking	Package	Weight	Base qty	Delivery mode
BAR46	S46	SOT-23	0.01g	3000	Tape & reel
BAR46AFILM	A46	SOT-23	0.01g	3000	Tape & reel

- Epoxy meets UL94,V0

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a registered trademark of STMicroelectronics

© 2002 STMicroelectronics - Printed in Italy - All rights reserved.

STMicroelectronics GROUP OF COMPANIES

Australia - Brazil - Canada - China - Finland - France - Germany  
Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Singapore  
Spain - Sweden - Switzerland - United Kingdom - United States.

<http://www.st.com>





**ООО «НИОКРсистемс»** - это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

### **Наша компания это:**

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование
- Работаем по 275 ФЗ