

NPN Silicon Double Transistor



- To be used as a current mirror
- Good thermal coupling and V_{BE} matching
- High current gain
- Low collector-emitter saturation voltage
- Pb-free (RoHS compliant) package
- Qualified according AEC Q101



Type	Marking	Pin Configuration				Package
BCV61B	1Ks	1 = C2	2 = C1	3 = E1	4 = E2	SOT143
BCV61C	1Ls	1 = C2	2 = C1	3 = E1	4 = E2	SOT143

Maximum Ratings

Parameter	Symbol	Value	Unit
Collector-emitter voltage (transistor T1)	V_{CEO}	30	V
Collector-base voltage (open emitter) (transistor T1)	V_{CBO}	30	
Emitter-base voltage	V_{EBS}	6	
DC collector current	I_C	100	mA
Peak collector current, $t_p < 10$ ms	I_{CM}	200	
Base peak current (transistor T1)	I_{BM}	200	
Total power dissipation, $T_S = 99$ °C	P_{tot}	300	mW
Junction temperature	T_j	150	°C
Storage temperature	T_{stg}	-65 ... 150	

Thermal Resistance

Junction - soldering point[1)]	R_{thJS}	≤170	K/W

[1]For calculation of R_{thJA} please refer to Application Note AN077 (Thermal Resistance Calculation)

Electrical Characteristics at T_A = 25°C, unless otherwise specified

Parameter	Symbol	Values			Unit
		min.	typ.	max.	
DC Characteristics of T1					
Collector-emitter breakdown voltage I_C = 10 mA, I_B = 0	$V_{(BR)CEO}$	30	-	-	V
Collector-base breakdown voltage I_C = 10 µA, I_E = 0	$V_{(BR)CBO}$	30	-	-	
Emitter-base breakdown voltage I_E = 10 µA, I_C = 0	$V_{(BR)EBO}$	6	-	-	
Collector cutoff current V_{CB} = 30 V, I_E = 0	I_{CBO}	-	-	15	nA
Collector cutoff current V_{CB} = 30 V, I_E = 0 , T_A = 150 °C	I_{CBO}	-	-	5	µA
DC current gain[1)] I_C = 0.1 mA, V_{CE} = 5 V	h_{FE}	100	-	-	-
DC current gain[1)] I_C = 2 mA, V_{CE} = 5 V, BCV61B I_C = 2 mA, V_{CE} = 5 V, BCV61C	h_{FE}	 200 420	 290 520	 450 800	
Collector-emitter saturation voltage[1)] I_C = 10 mA, I_B = 0.5 mA I_C = 100 mA, I_B = 5 mA	V_{CEsat}	 - -	 90 200	 250 600	mV
Base-emitter saturation voltage[1)] I_C = 10 mA, I_B = 0.5 mA I_C = 100 mA, I_B = 5 mA	V_{BEsat}	 - -	 700 900	 - -	
Base-emitter voltage[1)] I_C = 2 mA, V_{CE} = 5 V I_C = 10 mA, V_{CE} = 5 V	$V_{BE(ON)}$	 580 -	 660 -	 700 770	


[1]Puls test: $t \leq 300$ µs, D = 2%

Electrical Characteristics at T_A = 25°C, unless otherwise specified.

Parameter	Symbol	Values			Unit
		min.	typ.	max.	
Characteristics					
Base-emitter forward voltage	V_{BES}				V
I_E = 10 µA		0.4	-	-	
I_E = 250 mA		-	-	1.8	
Matching of transistor T1 and transistor T2	I_{C1} / I_{C2}				-
at I_{E2} = 0.5mA and V_{CE1} = 5V		-	-	-	
T_A = 25 °C		0.7	-	1.3	
T_A = 150 °C		0.7	-	1.3	
Thermal coupling of transistor T1 and transistor T2 [1] T1: V_{CE} = 5V Maximum current of thermal stability of I_{C1}	I_{E2}	-	5	-	mA
AC characteristics for transistor T1					
Transition frequency	f_T	-	250	-	MHz
I_C = 10 mA, V_{CE} = 5 V, f = 100 MHz					
Collector-base capacitance	C_{cb}	-	0.95	-	pF
V_{CB} = 10 V, f = 1 MHz					
Emitter-base capacitance	C_{eb}	-	9	-	
V_{EB} = 0.5 V, f = 1 MHz					
Noise figure	F	-	2	-	dB
I_C = 200 µA, V_{CE} = 5 V, R_S = 2 kΩ, f = 1 kHz, Δ f = 200 Hz					
Short-circuit input impedance	h_{11e}	-	4.5	-	kΩ
I_C = 1 mA, V_{CE} = 10 V, f = 1 kHz					
Open-circuit reverse voltage transf.ratio	h_{12e}	-	2	-	10^{-4}
I_C = 1 mA, V_{CE} = 10 V, f = 1 kHz					
Short-circuit forward current transf.ratio	h_{21e}	100	-	900	-
I_C = 1 mA, V_{CE} = 10 V, f = 1 kHz					
Open-circuit output admittance	h_{22e}	-	30	-	µS
I_C = 1 mA, V_{CE} = 10 V, f = 1 kHz					


1) Witout emitter resistor. Device mounted on alumina 15mm x 16.5mm x 0.7mm

Test circuit for current matching




Note: Voltage drop at contacts: V_{CO} < 2/3 V_T = 16mV

Characteristic for determination of V_{CE1} at specified R_E range with I_{E2} as parameter under condition of I_{C1}/I_{E2} = 1.3




Note: BCV61 with emitter resistors

Collector-base capacitance $C_{cb} = f(V_{CB})$
Emitter-base capacitance $C_{eb} = f(V_{EB})$




Total power dissipation $P_{tot} = f(T_S)$




Permissible pulse load


$P_{totmax} / P_{totDC} = f(t_p)$




Package Outline



Foot Print




Marking Layout (Example)



Standard Packing

Reel ø180 mm = 3.000 Pieces/Reel
Reel ø330 mm = 10.000 Pieces/Reel



Edition 2009-11-16

Published by
Infineon Technologies AG
81726 Munich, Germany

© 2009 Infineon Technologies AG
All Rights Reserved.

Legal Disclaimer

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

Information

For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office (<www.infineon.com>).

Warnings

Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office.
Infineon Technologies components may be used in life-support devices or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.

ООО «НИОКРсистемс» - это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

Наша компания это:

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование
- Работаем по 275 ФЗ

ООО «НИОКР СИТЕМС»
Москва, 125362, Россия, ул. Вишневая, д. 9, к. 1, Блок 104 а и 104 в

Телефон: 8 (495) 268-14-82
Email: n@nsistems.ru

ИНН: 7735154786
ОГРН: 1167746717709