THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

PANDUIT PART NUMBER **	PANEL THICKNESS	A ±0.013 (0.33)	B ±0.015 (0.38)	C +0.020 (0.51) -0.015 (0.38)	D +0.020 (0.51) -0.015 (0.38)	E REF.	F ±TOL.	G REF.	R REF.
GE_62F-A-C	0.036 - 0.062 (0.91 - 1.57)	0.031 (0.79)	0.070 (1.78)	0.130 (3.30)	0.030 (0.76)	0.131 (3.33)	0.105 +0.005 (0.13) (2.67) -0.025 (0.64)	0.150 (3.81)	0.06 (1.52)
GE_99F-A-C	0.062 - 0.099 (1.57 - 2.51)	0.049 (1.24)	0.108 (2.74)	0.155 (3.94)	0.030 (0.76)	0.169 (4.29)	0.125 +0.005 (0.13) (3.18) -0.025 (0.64)	0.150 (3.81)	0.06 (1.52)
GE_144F-A-C	0.099 - 0.144 (2.51 - 3.66)	0.080 (2.03)	0.152 (3.86)	0.192 (4.88)	0.030 (0.76)	0.213 (5.41)	0.160 +0.005 (0.13) (4.06) -0.035 (0.89)	0.150 (3.81)	0.06 (1.52)

NOTES:

* 1) DIM'S F & G APPLY ONLY TO SLOTTED GROMMET EDGING.

** 2) PART NO. EXAMPLE:

GE S 62 F - A - C 0


- GE: GROMMET EDGING
- S: S=SOLID, E=SLOTTED
- 62: MAX. PANEL THICKNESS
- F: F=POLYETHYLENE
- A: A=ADHESIVE
- C: 100 FOOT ROLL
- 0: WEATHER RESISTANT BLACK


3) SEE CURRENT PRICE SHEET FOR PART NO. SUFFIX DESIGNATION FOR PACKAGE SIZE.

4) COLOR: a) NATURAL
b) -0 AFTER PART NO. DENOTES WEATHER RESISTANT BLACK

5) THE ADHESIVE WIDTH IS TO STRETCH COMPLETELY ACROSS THE PRODUCT PROFILE.

6) SLOTTED WALL STYLE IS RECOMMENDED FOR INSIDE PANEL CUT OUTS.
SOLID WALL STYLE IS RECOMMENDED FOR STRAIGHT, OUTSIDE EDGES.





REV	DATE	BY	CHK	DESCRIPTION	ECN - R	CUST	SUP	QC
6	10/18/11	SHOR	VJS	ADDED TOLERANCES FOR A, B, C, & F	GB0308BA 6	RAMI		
5	10/27/03	JAD		UPDATED DIM 'A' FOR EACH PRODUCT	GB0308BA 5			
4	6/12/02	LGG		REVISED DIM 'F' TO REFERENCE	GB0308BA 4			
3	3/19/02	LGG		REMOVED NOTE '5' AND RENUMBERED. ADDED REF TO 'G' DIM REMOVED 'MAX. FROM 'R' DIM & ADDED ADHESIVE THICKNESS.	GB0308BA 3			
2	08/05/98	CPE		CAD FILE RENAMED, ADDED NOTE #7	GB0308BA 2			
1	04/28/97	CPE		CAD FILE RENAMED PER CURRENT NAMING CONVETION	GB0308BA 1			
				GES36F-A-C WAS REMOVED AS THIS PART IS NOT BEING SET UP				
R	02/17/93	CPE		INITIAL RELEASE	GB0308BA R			

(DIMENSIONS IN PARENTHESES ARE IN METRIC.)

CAD FILENAME/LAYERS: G00308BA_DC_ADHGROMMEDG_05

PANDUIT CORP. TINLEY PARK, ILLINOIS

ADHESIVE LINED GROMMET EDGING

UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE:
(.X) ±0.1(2.5) (.XXX) ± 0.020(.5)
(.XX) ±0.05(1.3) ANGLES ± 5°

UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE GIVEN IN INCHES, THIRD ANGLE PROJECTION.

DRAWN BY	MAT'L:	SCALE
CPE	SEE NOTE #2	NONE
DATE: 02/17/93		DRAWING NO.: GB0308BA
CHK'D		DWG SIZE: A

ООО «НИОКРсистемс» - это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

Наша компания это:

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование
- Работаем по 275 ФЗ

ООО «НИОКР СИТЕМС»
Москва, 125362, Россия, ул. Вишневая, д. 9, к. 1, Блок 104 а и 104 в

Телефон: 8 (495) 268-14-82
Email: n@nsistems.ru

ИНН: 7735154786
ОГРН: 1167746717709