DUAL N-CHANNEL ENHANCEMENT MODE MOSFET

Features

- Dual N-Channel MOSFET
- Low On-Resistance
- Low Gate Threshold Voltage
- Low Input Capacitance
- Fast Switching Speed
- Low Input/Output Leakage
- Ultra-Small Surface Mount Package
- **Lead Free By Design/RoHS Compliant (Note 1)**
- **"Green" Device (Note 2)**
- **Qualified to AEC-Q101 Standards for High Reliability**

Mechanical Data

- Case: SOT563
- Case Material: Molded Plastic, "Green" Molding Compound. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminal Connections: See Diagram (Note 3)
- Terminals: Finish - Matte Tin annealed over Copper leadframe. Solderable per MIL-STD-202, Method 208
- Weight: 0.003 grams (approximate)

SOT563

Top View



2N7002VC
(ASK Marking Code)



2N7002VAC
(AYK Marking Code)

Ordering Information (Note 4)

Part Number	Case	Packaging
2N7002VC-7	SOT563	3000/Tape & Reel
2N7002VAC-7	SOT563	3000/Tape & Reel

Notes:
1. No purposefully added Lead.
2. Diodes Inc.'s "Green" policy can be found on our website at http://www.diodes.com.
3. Package is non-polarized. Parts may be on reel in orientation illustrated, 180° rotated, or mixed (both ways).
4. For packaging details, go to our website at http://www.diodes.com.

Marking Information



ASK = 2N7002VC Product Type Marking Code (See Note 1)
YM = Date Code Marking
Y = Year ex: R = 2004
M = Month ex: 9 = September



AYK = 2N7002VAC Product Type Marking Code (See Note 1)
YM = Date Code Marking
Y = Year ex: R = 2004
M = Month ex: 9 = September

Date Code Key

Year	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017
Code	R	S	T	U	V	W	X	Y	Z	A	B	C	D	E

Month	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Code	1	2	3	4	5	6	7	8	9	O	N	D

© Diodes Incorporated

Maximum Ratings @T_A = 25°C unless otherwise specified

Characteristic		Symbol	Value	Units
Drain-Source Voltage		V_{DSS}	60	V
Drain-Gate Voltage $R_{GS} \leq 1.0M\Omega$		V_{DGR}	60	V
Gate-Source Voltage (Note 5)	Continuous Pulsed	V_{GSS}	±20 ±40	V
Drain Current (Note 5)	Continuous	I_D	280	mA
Drain Current (Note 5)	Pulsed	I_{DM}	1.5	A

Thermal Characteristics @T_A = 25°C unless otherwise specified

Characteristic	Symbol	Value	Units
Total Power Dissipation	P_D	150	mW
Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	833	°C/W
Operating and Storage Temperature Range	T_J, T_{STG}	-55 to +150	°C

Electrical Characteristics @T_A = 25°C unless otherwise specified

Characteristic		Symbol	Min	Typ	Max	Unit	Test Condition
OFF CHARACTERISTICS (Note 6)							
Drain-Source Breakdown Voltage		BV_{DSS}	60	70	—	V	V_{GS} = 0V, I_D = 10μA
Zero Gate Voltage Drain Current	@ T_C = 25°C @ T_C = 125°C	I_{DSS}	— —	— —	1.0 500	μA	V_{DS} = 60V, V_{GS} = 0V
Gate-Body Leakage		I_{GSS}	—	—	±100	nA	V_{GS} = ±20V, V_{DS} = 0V
ON CHARACTERISTIC (Note 6)							
Gate Threshold Voltage		$V_{GS(th)}$	1.0	—	2.5	V	V_{DS} = V_{GS}, I_D = 250μA
Static Drain-Source On-Resistance		$R_{DS\ (ON)}$	— —	— —	7.5 13.5	Ω	V_{GS} = 5V, I_D = 0.05A, V_{GS} = 10V, I_D = 0.5A, T_j = 125°C
On-State Drain Current		$I_{D(ON)}$	0.5	1.0	—	A	V_{GS} = 10V, V_{DS} = 7.5V
Forward Transconductance		g_{FS}	80	—	—	mS	V_{DS} = 10V, I_D = 0.2A
DYNAMIC CHARACTERISTICS							
Input Capacitance		C_{iss}	—	—	50	pF	V_{DS} = 25V, V_{GS} = 0V, f = 1.0MHz
Output Capacitance		C_{oss}	—	—	25	pF	
Reverse Transfer Capacitance		C_{rss}	—	—	5.0	pF	
SWITCHING CHARACTERISTICS							
Turn-On Delay Time		$t_{D(ON)}$	—	—	20	ns	V_{DD} = 30V, I_D = 0.2A, R_L = 150Ω,
Turn-Off Delay Time		$t_{D(OFF)}$	—	—	20	ns	V_{GEN} = 10V, R_{GEN} = 25Ω

Notes: 5. Device mounted on FR-4 PCB, 1 inch x 0.85 inch x 0.062 inch; pad layout as shown on Diodes Inc. suggested pad layout document AP02001, which can be found on our website at http://www.diodes.com.
6. Short duration pulse test used to minimize self-heating effect.

© Diodes Incorporated



Fig. 1, Derating Curve - Total

Package Outline Dimensions



SOT563			
Dim	**Min**	**Max**	**Typ**
A	0.15	0.30	0.20
B	1.10	1.25	1.20
C	1.55	1.70	1.60
D	-	-	0.50
G	0.90	1.10	1.00
H	1.50	1.70	1.60
K	0.55	0.60	0.60
L	0.10	0.30	0.20
M	0.10	0.18	0.11
All Dimensions in mm			

Suggested Pad Layout



Dimensions	Value (in mm)
Z	2.2
G	1.2
X	0.375
Y	0.5
C1	1.7
C2	0.5

© Diodes Incorporated

IMPORTANT NOTICE

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

LIFE SUPPORT

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or
2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2011, Diodes Incorporated

www.diodes.com

НИОКР СИСТЕМС

ООО «НИОКРсистемс» - это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

Наша компания это:

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование
- Работаем по 275 ФЗ

ООО «НИОКР СИТЕМС»
Москва, 125362, Россия, ул. Вишневая, д. 9, к. 1, Блок 104 а и 104 в

Телефон: 8 (495) 268-14-82
Email: n@nsistems.ru

ИНН: 7735154786
ОГРН: 1167746717709