2N6036
2N6039

Complementary power Darlington transistors

Features


- Good h_{FE} linearity
- High f_T frequency
- Monolithic Darlington configuration with integrated antiparallel collector-emitter diode

Applications

- Linear and switching industrial equipment


Description

The devices are manufactured in planar technology with “base island” layout and monolithic Darlington configuration.



SOT-32

Figure 1. Internal schematic diagram



R_1 typ. = 15 kΩ R_2 typ. = 100 Ω

Table 1. Device summary

Order codes	Marking	Polarity	Package	Packaging
2N6036	2N6036	NPN	SOT-32	Tube
2N6039	2N6039	PNP	SOT-32	Tube

1 Absolute maximum ratings

Table 2. Absolute maximum ratings

Symbol	Parameter	Value	Unit
V_{CBO}	Collector-base voltage (I_E = 0)	80	V
V_{CEO}	Collector-emitter voltage (I_B = 0)		
V_{EBO}	Emitter-base voltage (I_C = 0)	5	V
I_C	Collector current	4	A
I_{CM}	Collector peak current	8	A
I_B	Base current	0.1	A
P_{TOT}	Total dissipation at T_{case} = 25°C	40	W
T_{STG}	Storage temperature	-65 to 150	°C
T_J	Max. operating junction temperature	150	°C

Note: For PNP types voltage and current values are negative.

2 Electrical characteristics

(T_{case} = 25 °C; unless otherwise specified)

Table 3. Electrical characteristics

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
I_{CEV}	Collector cut-off current (V_{BE} = -1.5 V)	V_{CE} = 80 V V_{CE} = 80 V, T_c = 125 °C		-	0.1 0.5	mA mA
I_{CBO}	Collector cut-off current (I_E = 0)	V_{CB} = 80 V		-	0.1	mA
I_{CEO}	Collector cut-off current (I_B = 0)	V_{CE} = 80 V		-	0.1	mA
I_{EBO}	Emitter cut-off current (I_C = 0)	V_{EB} = 5 V		-	2	mA
$V_{CEO(sus)}$ (1)	Collector-emitter sustaining voltage	I_C = 100 mA	80	-		V
$V_{CE(sat)}$ (1)	Collector-emitter saturation voltage	I_C = 2 A I_B = 8 mA		-	2	V
		I_C = 4 A I_B = 40 mA		-	3	
$V_{BE(sat)}$ (1)	Base-emitter saturation voltage	I_C = 4 A I_B = 40 mA		-	4	V
$V_{BE(on)}$	Base-emitter on voltage	I_C = 2 A V_{CE} = 3 V		-	2.8	V
h_{FE} (1)	DC current gain	I_C = 0.5 A V_{CE} = 3 V	500	-		
		I_C = 2 A V_{CE} = 3 V	750	-	15000	
		I_C = 4 A V_{CE} = 3 V	100	-		
h_{fe}	Small signal current gain	I_C = 0.75 A V_{CE} = 10 V f = 1 MHz	25	-		
C_{CBO}	Collector base capacitance (I_E = 0)	V_{CB} = 10 V f = 0.1 MHz for 2N6036 for 2N6039		-	100 200	pF pF

1. Pulsed duration = 300 µs, duty cycle 1.5%.

Note: For PNP types voltage and current values are negative.

2.1 Typical characteristic (curves)

Figure 2. DC current gain (V_{CE} = 3 V NPN)




Figure 3. DC current gain (V_{CE} = - 3 V PNP)




Figure 4. DC current gain (V_{CE} = 5 V NPN)




Figure 5. DC current gain (V_{CE} = - 5 V PNP)




Figure 6. Collector-emitter saturation voltage (NPN)




Figure 7. Collector-emitter saturation voltage (PNP)




Figure 8. Base-emitter saturation voltage (NPN)




Figure 9. Base-emitter saturation voltage (PNP)




Figure 10. Base-emitter on voltage (NPN)




Figure 11. Base-emitter on voltage (PNP)




Figure 12. Resistive load switching time (NPN, on)




Figure 13. Resistive load switching time (PNP, on)




Figure 14. Resistive load switching time (NPN, off)





Figure 15. Resistive load switching time (PNP, off)




3 Package mechanical data

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: *www.st.com*.
ECOPACK® is an ST trademark.

SOT-32 (TO-126) MECHANICAL DATA

DIM.	mm.		
	MIN.	TYP	MAX.
A	2.4		2.9
B	0.64		0.88
B1	0.39		0.63
D	10.5		11.05
E	7.4		7.8
e	2.04	2.29	2.54
e1	4.07	4.58	5.08
L	15.3		16
P	2.9		3.2
Q		3.8	
Q1	1		1.52
H2		2.15	
I		1.27	



1 = BASE
2 = COLLECTOR
3 = EMITTER

0016114E

4 Revision history

Table 4. Document revision history

Date	Revision	Changes
21-Jun-2004	4	Document migration, no content change.
20-May-2009	5	Modified SOT-32 mechanical data.

Please Read Carefully:

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST’s terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

UNLESS OTHERWISE SET FORTH IN ST’S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

UNLESS EXPRESSLY APPROVED IN WRITING BY AN AUTHORIZED ST REPRESENTATIVE, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER’S OWN RISK.

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2009 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Philippines - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com

ООО «НИОКРсистемс» - это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

Наша компания это:

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование
- Работаем по 275 ФЗ

ООО «НИОКР СИТЕМС»
Москва, 125362, Россия, ул. Вишневая, д. 9, к. 1, Блок 104 а и 104 в

Телефон: 8 (495) 268-14-82
Email: n@nsistems.ru

ИНН: 7735154786
ОГРН: 1167746717709