

## FEATURES

- Rugged vitreous enamel coating withstands high humidity and temperature cycling.
- Durable construction, recommended for industrial applications where reliability is paramount.
- All-welded construction.
- Flame resistant lead free vitreous enamel coating.
- RoHS compliant; Add "E" suffix to part number to specify.

## SPECIFICATIONS

### Material

**Coating:** Conformal lead free vitreous enamel.

**Core:** Ceramic.

**Terminals:** Solder-coated axial.  
RoHS solder composition is 96% Sn, 3.5% Ag, 0.5% Cu

### Derating

Linearly from  
100% @ +25°C to  
0% @ +350°C.

### Electrical

**Tolerance:** ±5% standard.  
Other tolerances available.

**Power rating:** Based on 25°C free air rating (other wattages available).

### Overload:

Under 7 watts: 5 times rated wattage for 5 seconds.  
7 watts and over: 10 times rated wattage for 5 seconds.


### Temperature coefficient:

1 to 9.99 ohms: ±50 ppm/°C  
10 ohms and over: ±30 ppm/°C



# 20 Series

## Vitreous Enamel Conformal Axial Terminal Wirewound, 5% Tolerance Standard



Series	Wattage	Ohms	Dimensions (in./mm max.)		Max. Volt.**	Lead ga.
			Length*	Diam.*		
21	1	1.0-3.0K	0.421 / 10.7	0.156 / 4.0	75	24
22	2	1.0-3.0K	0.421 / 10.7	0.219 / 5.6	65	20
23	3	0.1-10K	0.515 / 13.1	0.220 / 5.6	135	20
25	5	0.1-28K	1.015 / 25.8	0.276 / 7.0	330	20
27	7	0.1-25K	1.265 / 32.1	0.394 / 10.0	450	20
20	10	0.1-100K	1.859 / 47.2	0.394 / 10.0	720	20

12.5 watt size available on special order

\*For units below 1Ω, add 15% to body diameter, 10% to body length.

\*\*Maximum Voltage is based on Ohm's Law  $[V=\sqrt{P \cdot R}]$  as limited by the resistance value of specified product

The 20 Series axial terminal resistors are both durable and economical. They have all the electrical attributes of the more expensive 90 Series resistors, including all-welded construction.

They offer the durability of a lead free conformal vitreous enamel coating and are ideal for computer, communications and industrial applications in which cost, quality, and reliability are key considerations.

## ORDERING INFORMATION

RoHS Compliant

**21JR10E**

<b>20 Series</b>	<b>Wattage</b>	<b>Tolerance</b>	<b>Resistance Value</b>
Vitreous Enamel	1 = 1W	J = 5%	R10 = 0.10Ω
Axial Lead	2		1R0 = 1.0Ω
Wirewound	3		10R = 10.0Ω
	5		250 = 250Ω
	7		1K0 = 1,000Ω
	0 = 10W		4K5 = 4,500Ω
			50K = 50,000Ω

Check product availability at [ohmite.com](http://ohmite.com)

## STANDARD PART NUMBERS FOR 20 SERIES

Ohmic value	Part No. Prefix Suffix	Wattage						Ohmic value	Part No. Prefix Suffix	Wattage						Ohmic value	Part No. Prefix Suffix	Wattage					
		1	2	3	5	7	10			1	2	3	5	7	10			1	2	3	5	7	10
0.10 — R10			✓	✓	✓	✓	✓	62 — 62R	✓	✓	✓	✓	✓	✓	1,800 — 1K8	✓	✓	✓	✓	✓	✓		
0.13 — R13			✓	✓	✓	✓	✓	68 — 68R	✓	✓	✓	✓	✓	✓	2,000 — 2K0	✓	✓	✓	✓	✓	✓		
0.15 — R15			✓	✓	✓	✓	✓	75 — 75R	✓	✓	✓	✓	✓	✓	2,200 — 2K2	✓	✓	✓	✓	✓	✓		
0.20 — R20			✓	✓	✓	✓	✓	82 — 82R	✓	✓	✓	✓	✓	✓	2,500 — 2K5	✓	✓	✓	✓	✓	✓		
0.25 — R25			✓	✓	✓	✓	✓	100 — 100	✓	✓	✓	✓	✓	✓	2,700 — 2K7	✓	✓	✓	✓	✓	✓		
0.30 — R30			✓	✓	✓	✓	✓	120 — 120	✓	✓	✓	✓	✓	✓	3,000 — 3K0	✓	✓	✓	✓	✓	✓		
0.33 — R33			✓	✓	✓	✓	✓	125 — 125	✓	✓	✓	✓	✓	✓	3,300 — 3K3	✓	✓	✓	✓	✓	✓		
0.50 — R50			✓	✓	✓	✓	✓	150 — 150	✓	✓	✓	✓	✓	✓	3,500 — 3K5	✓	✓	✓	✓	✓	✓		
0.75 — R75			✓	✓	✓	✓	✓	180 — 180	✓	✓	✓	✓	✓	✓	3,900 — 3K9	✓	✓	✓	✓	✓	✓		
1 — 1R0	✓	✓	✓	✓	✓	✓	✓	200 — 200	✓	✓	✓	✓	✓	✓	4,000 — 4K0	✓	✓	✓	✓	✓	✓		
1.5 — 1R5	✓	✓	✓	✓	✓	✓	✓	220 — 220	✓	✓	✓	✓	✓	✓	4,500 — 4K5	✓	✓	✓	✓	✓	✓		
2 — 2R0	✓	✓	✓	✓	✓	✓	✓	225 — 225	✓	✓	✓	✓	✓	✓	4,700 — 4K7	✓	✓	✓	✓	✓	✓		
2.2 — 2R2	✓	✓	✓	✓	✓	✓	✓	250 — 250	✓	✓	✓	✓	✓	✓	5,000 — 5K0	✓	✓	✓	✓	✓	✓		
3 — 3R0	✓	✓	✓	✓	✓	✓	✓	270 — 270	✓	✓	✓	✓	✓	✓	6,000 — 6K0	✓	✓	✓	✓	✓	✓		
4 — 4R0	✓	✓	✓	✓	✓	✓	✓	300 — 300	✓	✓	✓	✓	✓	✓	6,800 — 6K8	✓	✓	✓	✓	✓	✓		
5 — 5R0	✓	✓	✓	✓	✓	✓	✓	330 — 330	✓	✓	✓	✓	✓	✓	7,000 — 7K0	✓	✓	✓	✓	✓	✓		
7.5 — 7R5	✓	✓	✓	✓	✓	✓	✓	350 — 350	✓	✓	✓	✓	✓	✓	7,500 — 7K5	✓	✓	✓	✓	✓	✓		
10 — 10R	✓	✓	✓	✓	✓	✓	✓	390 — 390	✓	✓	✓	✓	✓	✓	8,000 — 8K0	✓	✓	✓	✓	✓	✓		
12 — 12R	✓	✓	✓	✓	✓	✓	✓	400 — 400	✓	✓	✓	✓	✓	✓	9,000 — 9K0	✓	✓	✓	✓	✓	✓		
15 — 15R	✓	✓	✓	✓	✓	✓	✓	450 — 450	✓	✓	✓	✓	✓	✓	10,000 — 10K	✓	✓	✓	✓	✓	✓		
18 — 18R	✓	✓	✓	✓	✓	✓	✓	470 — 470	✓	✓	✓	✓	✓	✓	12,000 — 12K	✓	✓	✓	✓	✓	✓		
20 — 20R	✓	✓	✓	✓	✓	✓	✓	500 — 500	✓	✓	✓	✓	✓	✓	13,000 — 13K	✓	✓	✓	✓	✓	✓		
22 — 22R	✓	✓	✓	✓	✓	✓	✓	560 — 560	✓	✓	✓	✓	✓	✓	15,000 — 15K	✓	✓	✓	✓	✓	✓		
25 — 25R	✓	✓	✓	✓	✓	✓	✓	600 — 600	✓	✓	✓	✓	✓	✓	17,000 — 17K	✓	✓	✓	✓	✓	✓		
27 — 27R	✓	✓	✓	✓	✓	✓	✓	680 — 680	✓	✓	✓	✓	✓	✓	20,000 — 20K	✓	✓	✓	✓	✓	✓		
30 — 30R	✓	✓	✓	✓	✓	✓	✓	750 — 750	✓	✓	✓	✓	✓	✓	22,000 — 22K	✓	✓	✓	✓	✓	✓		
33 — 33R	✓	✓	✓	✓	✓	✓	✓	800 — 800	✓	✓	✓	✓	✓	✓	25,000 — 25K	✓	✓	✓	✓	✓	✓		
35 — 35R	✓	✓	✓	✓	✓	✓	✓	820 — 820	✓	✓	✓	✓	✓	✓	30,000 — 30K	✓	✓	✓	✓	✓	✓		
39 — 39R	✓	✓	✓	✓	✓	✓	✓	900 — 900	✓	✓	✓	✓	✓	✓	33,000 — 33K	✓	✓	✓	✓	✓	✓		
40 — 40R	✓	✓	✓	✓	✓	✓	✓	1,000 — 1K0	✓	✓	✓	✓	✓	✓	35,000 — 35K	✓	✓	✓	✓	✓	✓		
47 — 47R	✓	✓	✓	✓	✓	✓	✓	1,100 — 1K1	✓	✓	✓	✓	✓	✓	40,000 — 40K	✓	✓	✓	✓	✓	✓		
50 — 50R	✓	✓	✓	✓	✓	✓	✓	1,200 — 1K2	✓	✓	✓	✓	✓	✓	50,000 — 50K	✓	✓	✓	✓	✓	✓		
56 — 56R	✓	✓	✓	✓	✓	✓	✓	1,500 — 1K5	✓	✓	✓	✓	✓	✓									

✓ = Standard values

✦ = Non-standard values subject to minimum handling charge per item

Shaded values involve very fine resistance wire and should not be used in critical applications without burn-in and/or thermal cycling.



**ООО «НИОКРсистемс»** - это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

### **Наша компания это:**

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование
- Работаем по 275 ФЗ