



Screw Clamp Connections


Spring Loaded




RSF 3



RSF 1



Available Options		Version	Part No.		Part No.
Molding material		TS 32 Polyamide	0497560000		
		TS 35 Polyamide	9501160000		
		TS 32 Melamine			0270320000
Dimensions					
Width / Length / Height mm (in.)		with TS 32		8/50/60 (.31/1.97/2.36)	11/50/60 (.43/1.97/2.36)
Insulating stripping length		mm (in.)	12 (.47)		12 (.47)
Technical Data					
Rated voltage / rated current / wire size		UL	600 V / 25 A / #22...12 AWG		600 V / 40 A / #14...8 AWG
		CSA	600 V / 25 A / #22...12 AWG		300 V / 50 A / #14...8 AWG
Terminal Rail (2 m)			Type	Part No.	Type
		Steel	TS 32	0122800000	TS 32
		Steel (M6 Slots)	TS 32	0676100000	TS 32
Locking pin (1 m)—optional		Steel	SST 3	0152700000	SST 3
End Bracket (thickness mm)					
			EWK 1 (8.5)	0206160000	EWK I (85)
End Plate (thickness mm)					
		Polyamide	AP (3)	0270460000	
		Melamine			AP (3)
Partition (thickness mm)					
		Polyamide	TW (1.5)	3877960000	
		Resin bonded paper	TW (2)	3833500000	TW (2)
		Resin bonded paper	TW (0.5)	0474700000	TW (0.5)
Small partition		Polyamide	TSch 1	0319160000	
Jumper					
	Note: Final number in model indicates no. of poles (e.g. QL 2 = 2 poles). For additional information, see Accessories section.		QL 2	0194300000	QL 2
			QL 3	0194400000	QL 3
			QL 4	0194500000	QL 4
			QL 10	0338300000	QL 10
			VH 13.5	0248500000	VH 17.5
			BS (M3 x 20)	0303000000	BS (M3 x 25)
		Sleeve			SS
		Screw			
		Washer			
Switching Link					
		2-way			VL 2
		Sleeve			VH 27
		Screw			BS (M3 x 35)
Test Plugs					
		Plug	PS (2.3Ø)	0180400000	PS (4Ø)
		Plug bolt	StB 14	0168600000	StB 18
Cover (1 m)					
		Transparent cover	ADP 2	0485300000	ADP 2
		Support bracket	HP 2	0485660000	HP 2
Hooked Blade Crimp*					
	#22...16 AWG		9100500000		9100200000
	#16...14 AWG		9100600000		9100300000
	#12...10 AWG				9100400000
Marking Tags					
All marking systems are shown in Accessories Section.			DEK 5/8	1653340001	DEK 5/8
			DEK 5/8	1653350001	DEK 5/8

*To accommodate two hooked bladed crimps back-to-back per terminal, one should be located in the current bar slot, the second through the lower part of the clamp.



ООО «НИОКРсистемс» - это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

Наша компания это:

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование
- Работаем по 275 ФЗ