LT-5™ Fast-Acting Fuse 662 Series

ELECTRICAL CHARACTERISTICS:

% of Ampere Rating	Time
150%	1 hour, Minimum
210%	30 minutes, **Max**imum
275%	.010 sec **Min.**; 3 sec **Max**
400%	.003 sec **Min.**; .030 sec **Max**
1000%	.020 sec **Max**imum

AGENCY APPROVALS: IEC 60127-3/1: VDE and Semko approved 50 mA through 3.15 A. Recognized under the Components Program Underwriters Laboratories and CSA accepted 40mA through 5A.

INTERRUPTING RATINGS: 35A or 10X rated current; whichever is greater.

ENVIRONMENTAL SPECIFICATIONS:

Operating Temperature: -40˚C to +85˚C.
Case Resistance: Min 100 Mohms, according to EIA/IS-722, 4.7
Vibration: 20gn, 20 min, 10Hz to 2,000Hz, 12 cycles according to EIA/IS-722, 4.10 (Frequency range 10-2000Hz, cross-over frequency 60 Hz according to IEC 60068-2-6, test Fc)
Mechanical Shock: 50g, half sine wave, 11ms, 3 times each direction according to IEC 60068-2-27.
Resistance to Cleaning Solvents: Clean according to EIA/IS-722, 4.11
Resistance to Soldering Heat: 10 sec. At 260˚C to IEC 60068-2-20, test Tb
Terminal Strength: Tensile load min. 9N, according to EIA/IS-722, 4.5.5


PHYSICAL SPECIFICATIONS:


Materials: Temperature Resistant Body, UL 94V-0; Sn Coated Copper Wire Terminals.
Solderability: IEC 60068-2-20, test Ta
Soldering Parameters: Wave Solder – 235˚C, 2 seconds maximum.

PACKAGING:

Please refer to the following suffixes when ordering:
- 100 Piece Bulk: Short Leads use suffix HXSL; Long Leads use suffix HXLL
- 750 Piece Tape and Reel per IEC 286-2: (Long Leads only) use suffix ZRLL
- 1000 Piece Ammo Pack use suffix MALL

PATENTED






ORDERING INFORMATION:

Catalog Number	Ampere Rating	Voltage Rating	Nominal Resistance Cold mOhms	Nominal Melting I^2t A^2 Sec
0662.040	.040	250	7500	0.00016
0662.050	.050	250	4483	0.00040
0662.063	.063	250	3866	0.001
0662.080	.080	250	2545	0.001
0662.100	.100	250	2010	0.002
0662.125	.125	250	1346	0.006
0662.160	.160	250	2960	0.014
0662.200	.200	250	2256	0.024
0662.250	.250	250	1460	0.058
0662.315	.315	250	1209	0.104
0662.400	.400	250	180	0.044
0662.500	.500	250	128	0.090
0662.630	.630	250	96	0.150
0662.800	.800	250	78	0.220
0662 001.	1.00	250	64	0.330
0662 1.25	1.25	250	45	0.680
0662 01.6	1.60	250	37	0.940
0662 002.	2.00	250	29	1.33
0662 02.5	2.50	250	24	1.94
0662 3.15	3.15	250	17	5.40
0662 004.	4.00	250	13	7.90
0662 005.	5.00	250	10	11.19

Refer to page 342 for LT-5™ holder information.

LT-5™ Fast-Acting Fuse 662 Series

Average Time Current Curves



ООО «НИОКРсистемс» - это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

Наша компания это:

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование
- Работаем по 275 ФЗ

ООО «НИОКР СИТЕМС»
Москва, 125362, Россия, ул. Вишневая, д. 9, к. 1, Блок 104 а и 104 в

Телефон: 8 (495) 268-14-82
Email: n@nsistems.ru

ИНН: 7735154786
ОГРН: 1167746717709