



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: BP192V12-3U

### BP192V12-3U - External Battery Pack for UPS System

#### Highlights

- Extends runtime of compatible Tripp Lite UPS Systems with 192VDC external battery connection
- Provides daisy-chain capability
- Simple installation; 3U rackmount, tower or stack adaptable



#### Description

Tripp Lite's BP192V12-3U rack/tower external battery pack offers extended battery runtime when used in conjunction with compatible Tripp Lite UPS systems. Multi-use form factor supports configuration in rackmount or stacking applications using only 3 rack spaces (3U). Upright tower configuration supported with optional 2-9USTAND accessory. Includes heavy-gauge cabling with high-current DC connectors for simple installation. Additional output connector allows multiple BP192V12-3U battery packs to be daisy-chained to the UPS for even longer extended run operation.

COMPATIBLE UPS SYSTEMS - SU5000RT4U, SU6000RT4U, SU8000RT4U, and other Tripp Lite UPS systems that specify the use of this battery pack.

#### Applications

- Ideal means of lengthening the battery runtime provided by compatible Tripp Lite UPS systems. Additional battery packs may be ordered at time of original UPS purchase or sourced at a later date to extend runtime performance if site power conditions deteriorate and longer battery runtime is desired.

#### Package Includes

- BP192V12-3U external battery pack
- Mounting hardware
- Warranty information
- Instruction manual

#### Features

- Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS systems
- Supports stacking or rackmount installation using only 3 rack spaces (3U)
- Supports upright tower installation with optional 2-9USTAND accessory (holds 3 battery packs in tower configuration)
- Set of two input/output connectors allows multiple BP192V12-3U battery packs to be daisy-chained to the UPS for even longer extended run operation
- Includes heavy-gauge cabling with high-current DC connectors for simple installation

#### Specifications

---

|                                         |                                                                                |
|-----------------------------------------|--------------------------------------------------------------------------------|
| <b>OUTPUT</b>                           |                                                                                |
| Overload protection                     | 50A DC output fuse                                                             |
| <b>INPUT</b>                            |                                                                                |
| UPS Input cord length (ft.)             | 36 in./9m, 8 AWG, 3 conductor                                                  |
| UPS Input cord length (m)               | 10.97                                                                          |
| <b>BATTERY</b>                          |                                                                                |
| Expandable battery runtime              | Includes a second input/output connector to daisy-chain multiple battery packs |
| DC system voltage (VDC)                 | 192                                                                            |
| Connects to UPS via                     | Detachable cable with UPS specific DC connector (90 cm length, 8 gauge)        |
| Typical battery lifespan                | 4-6 years typical (North America)                                              |
| <b>PHYSICAL</b>                         |                                                                                |
| Shipping weight (lbs)                   | 211.25                                                                         |
| Shipping weight (kg)                    | 95.9                                                                           |
| Unit Dimensions (HWD/in)                | 5.25 x 17.5 x 28                                                               |
| Unit Dimensions (HWD/cm)                | 13.3 x 44.5 x 71.1                                                             |
| Shipping Dimensions (HWD/in)            | 11.25 x 31.5 x 23                                                              |
| Shipping Dimensions (HWD/cm)            | 28.6 x 80 x 58.4                                                               |
| Unit weight (lbs)                       | 174                                                                            |
| Unit weight (kg)                        | 79                                                                             |
| Material of construction                | Black steel cabinet                                                            |
| Form factors supported                  | 3U rack/tower                                                                  |
| <b>WARRANTY</b>                         |                                                                                |
| Product Warranty Period (U.S. & Canada) | 2-year limited warranty                                                        |
| Product Warranty Period (International) | 1-year limited warranty                                                        |
| Product Warranty Period (Mexico)        | 1-year limited warranty                                                        |
| Product Warranty Period (Puerto Rico)   | 1-year limited warranty                                                        |
| Optional Coverage                       | 3 year, 5 year, next day and on-site warranty coverage available               |

Related Items

Optional Products

| Related Model                  | Description                                | Qty. |
|--------------------------------|--------------------------------------------|------|
| <a href="#">WEXT3-BP192V12</a> | 3-Year Extended Warranty - For BP192V12-3U | 1    |
| <a href="#">WEXT5-BP192V12</a> | 5-Year Extended Warranty - For BP192V12-3U | 1    |

|                              |                                                                                                     |   |
|------------------------------|-----------------------------------------------------------------------------------------------------|---|
| <a href="#">2-9USTAND</a>    | Enables Tower Placement of Rackmount UPS Systems                                                    | 1 |
| <a href="#">2POSTRMKITHD</a> | Enables 2-Post Rackmount Installation of 3U and Larger UPS, Transformer and Battery Pack Components | 1 |

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?variables.txtModelID=3139](http://www.tripplite.com/en/products/model.cfm?variables.txtModelID=3139).

---

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.



**ООО «НИОКРсистемс»** - это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

### **Наша компания это:**

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование
- Работаем по 275 ФЗ